




Dimensions	
Product dimensions (mm)	ø90 x 67
Packing dimensions (mm)	97 x 97 x 106
Net weight (g)	191
Gross weight (Kg)	0,223
Drilling hole (mm)	Ø75

Scheme

Scheme



### Small format adjustable downlight from the TROLL family Downled.

#### DESCRIPTION

Small format adjustable downlight from the TROLL family Downled setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for ceiling recessed installation. Luminaire body built in die-cast aluminium finished in black. Optical group is IP44 on the visible frontal area. Luminaire built-in an high efficiency faceted reflector made of high purity aluminium with an angle beam of 20°. Luminaire sets a 7 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 5 SMCD. Luminaire sets a ball joint system which allows tilting 20°. Fixture has a luminous flux of 483 Lm, with an efficiency of 69,0 Lm/W and a total consumption of 7 W. The average life for the luminaire is 35000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear Dimmable 1-10V fed at 220-240V; 50/60 Hz.

Item code	0147L/8420D/04
Product type	IN
Category	Recessed Downlights
Family	Downled
Subfamily	Downled
Materials	Luminaire body built in die-cast aluminium.
Optical system	Luminaire built-in a high efficiency faceted reflector made of high purity aluminium.
Installation instructions	Luminaire designed for ceiling recessed installation.
Pictograms	

Product	
Real power (W)	7
Real luminous flux (Lm)	483
Luminous efficiency (Lm/W)	69,0
Beam angle (°)	20
Life time (h)	35000
IP	44/20
Electrical class insulation	Class 2
Operating temperature	from -20° C to 35° C
Electrical feeding	220..240V, 50/60Hz
Colour	Black
Energy efficiency class	A

Control gear	
Control gear included	Yes
Control gear	1-10V Dimmable Electronic Control Gear
Factor de potencia	0,94

Light source	
Light source included	Yes
Light source	Led
Nominal power (W)	7
Nominal luminous flux (Lm)	700
Colour temperature (K)	4000
Colour consistency (SDCM)	5
CRI	80

Photometry

