




Dimensions

| | |
|-------------------------|----------|
| Product dimensions (mm) | Ø81 x 95 |
| Drilling hole (mm) | Ø75 |

Scheme

Scheme



Product

| | |
|-----------------------------|--------------------|
| IP | 20 |
| Electrical class insulation | Class 2 |
| Operating temperature | from -20°C to 35°C |
| Electrical feeding | 12 VDC |
| Colour | Gold |

Control gear

| | |
|-----------------------|----|
| Control gear included | No |
|-----------------------|----|

Light source

| | |
|-----------------------|--------------------------------|
| Light source included | No |
| Light source | Halogen or retrofit equivalent |

Accessories

| | |
|-----------|--|
| TRE/60/EL | 60W transformer with output at 12VDC from TROLL family standard. |
|-----------|--|

Adjustable round downlight from the TROLL family B.T. Z5.

DESCRIPTION

Adjustable round downlight from the TROLL family B.T. Z5 optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for ceiling recessed installation. Luminaire body built in die-cast aluminium finished in golden. Luminaire sets a ball joint system which allows tilting 30°. Use a MR16 lightsource with maximum power of 50 W. Lightsource not included. Luminaire is fed at 12V and needs auxiliary gear.

| | |
|---------------------------|---|
| Item code | 0147/12 |
| Product type | IN |
| Category | Recessed Downlights |
| Family | Bt |
| Subfamily | B.T. Z5 |
| Materials | Luminaire body built in die-cast aluminium. |
| Optical system | |
| Installation instructions | Luminaire designed for ceiling recessed installation. |