




#### Dimensions

Product dimensions (mm) 37 x 50 x 80

#### Scheme

#### Scheme



#### Product

Real power (W)	2,8
Real luminous flux (Lm)	115,2
Luminous efficiency (Lm/W)	41,1
Beam angle (°)	25
IP	20
Electrical class insulation	Class 1
Photobiological risk	0 - Exempt
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Stainless steel

#### Control gear

Control gear included	Yes
Control gear	Electronic Control Gear

#### Light source

Light source included	Yes
Light source	Led
Nominal power (W)	2,5
Nominal luminous flux (Lm)	150
Colour temperature (K)	3000
CRI	80

## Decorative minimalist sconce from the TROLL family Flex.

#### DESCRIPTION

Decorative minimalist sconce from the TROLL family Flex setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as Lighting hotel rooms. Designed for wall surface mounted. Luminaire body made from stainless steel sheet finished in chromed. Luminaire built-in a Polycarbonate opal diffuser with an angle beam of 120°. Luminaire sets a 2,5 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 115,2 Lm, with an efficiency of 41,1 Lm/W and a total consumption of 2,8 W. The average life for the luminaire is h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	0170/1/20
Product type	IN
Category	Apliques
Family	Flex
Subfamily	Flex
Materials	Luminaire body made from stainless steel sheet.
Optical system	Luminaire built-in a Polycarbonate opal diffuser.
Installation instructions	Luminaire designed for wall surface mounted.

#### Pictograms

