




Dimensions

Product dimensions (mm)	37 x 50 x 80
-------------------------	--------------

Scheme

Scheme



Product

Real power (W)	2,8
Real luminous flux (Lm)	115,2
Luminous efficiency (Lm/W)	41,1
Beam angle (°)	25
IP	20
Electrical class insulation	Class 1
Photobiological risk	0 - Exempt
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Stainless steel

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear

Light source

Light source included	Yes
Light source	Led
Nominal power (W)	2,5
Nominal luminous flux (Lm)	150
Colour temperature (K)	3000
CRI	80

Decorative minimalist sconce from the TROLL family Flex.

DESCRIPTION

Decorative minimalist sconce from the TROLL family Flex setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as Lighting hotel rooms. Designed for wall surface mounted. Luminaire body made from stainless steel sheet finished in chromed. Luminaire built-in a Polycarbonate opal diffuser with an angle beam of 120°. Luminaire sets a 2,5 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 115,2 Lm, with an efficiency of 41,1 Lm/W and a total consumption of 2,8 W. The average life for the luminaire is h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	0170/1/20
Product type	IN
Category	Apliques
Family	Flex
Subfamily	Flex
Materials	Luminaire body made from stainless steel sheet.
Optical system	Luminaire built-in a Polycarbonate opal diffuser.
Installation instructions	Luminaire designed for wall surface mounted.

Pictograms

