




Dimensions

Product dimensions (mm) \varnothing 315 x 420

Scheme

Scheme



Product

Real power (W)	28
Real luminous flux (Lm)	2138
Luminous efficiency (Lm/W)	76
Beam angle (°)	97
IP	20
Electrical class insulation	Class 1
Operating temperature	from 5°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	Grey

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear

Light source

Light source included	Yes
Light source	Led
Nominal power (W)	24
Nominal luminous flux (Lm)	3875
Average life time (h)	76000
Colour temperature (K)	4000
Colour consistency (SDCM)	2
CRI	85

Interior hanging luminary from the TROLL family Saturn.

DESCRIPTION

Interior hanging luminary from the TROLL family Saturn LED equipped in highly efficient LED sources. The luminary lampshade shall be made from polycarbonate. Luminary coffer made from aluminium profile. The light stream of the luminary used is 3000 lm. Colour temperature is 4000 K. Luminaire designed to be suspended from ceiling and suitable for illuminating recreational areas, halls, entrances, shops and shopping malls.

Item code	0D1ST130PC9
Product type	IN
Category	Surface Downlights
Family	Saturn
Subfamily	Saturn Led
Materials	Luminary lampshade shall be made from polycarbonate and Luminary coffer made from aluminium profile.
Optical system	Luminary sets a lampshade shall be made from polycarbonate.
Installation instructions	Luminaire designed to be suspended from the ceiling.
Pictograms	

