




#### Dimensions

Product dimensions (mm)      ø 315 x 420

#### Scheme

#### Scheme



#### Product

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 45                 |
| Real luminous flux (Lm)     | 3312               |
| Luminous efficiency (Lm/W)  | 73                 |
| Beam angle (°)              | 97                 |
| IP                          | 20                 |
| Electrical class insulation | Class 1            |
| Operating temperature       | from 5°C to 30°C   |
| Electrical feeding          | 220..240V, 50/60Hz |
| Colour                      | Grey               |

#### Control gear

|                       |                         |
|-----------------------|-------------------------|
| Control gear included | Yes                     |
| Control gear          | Electronic Control Gear |



#### Light source

|                            |       |
|----------------------------|-------|
| Light source included      | Yes   |
| Light source               | Led   |
| Nominal power (W)          | 37    |
| Nominal luminous flux (Lm) | 5720  |
| Average life time (h)      | 83000 |
| Colour temperature (K)     | 4000  |
| Colour consistency (SDCM)  | 2     |
| CRI                        | 85    |

## Interior hanging luminary from the TROLL family Saturn LED.

#### DESCRIPTION

Interior hanging luminary from the TROLL family Saturn LED equipped in highly efficient LED sources. The luminary lampshade shall be made from polycarbonate. Luminary coffer made from aluminium profile. The light stream of the luminary used is 5000 lm. Colour temperature is 4000 K. Luminaire designed to be suspended from ceiling and suitable for illuminating recreational areas, halls, entrances, shops and shopping malls

|                           |   |
|---------------------------|---|
| Item code                 | 0D1ST150PC9A  |
| Product type              | IN  |
| Category                  | Surface Downlights  |
| Family                    | Saturn  |
| Subfamily                 | Saturn Led  |
| Materials                 | Luminary lampshade shall be made from polycarbonate and Luminary coffer made from aluminium profile.  |
| Optical system            | Luminary sets a lampshade shall be made from polycarbonate.   |
| Installation instructions | Luminaire designed to be suspended from the ceiling.  |
| Pictograms                |   |