




Dimensions

Product dimensions (mm) \varnothing 315 x 410

Scheme

Scheme



Product

| | |
|-----------------------------|--------------------|
| Real power (W) | 28 |
| Real luminous flux (Lm) | 2734 |
| Upper hemisphere flux (%) | 98 |
| U.G.R. (%) | < 19 |
| Beam angle (°) | 80 |
| IP | 20 |
| Electrical class insulation | Class 1 |
| Operating temperature | from 5°C to 30°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | Grey |

Control gear

| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |

Light source

| | |
|----------------------------|-------|
| Light source included | Yes |
| Light source | Led |
| Nominal power (W) | 24 |
| Nominal luminous flux (Lm) | 3875 |
| Average life time (h) | 76000 |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | 2 |
| CRI | 85 |
| TM30RF | 80 |

Interior hanging luminaire from the TROLL family Saturn LED.

DESCRIPTION

Interior hanging luminaire from the TROLL family Saturn LED equipped in highly efficient LED sources. The luminaire lampshade shall be made from aluminium. Luminaire coffer made from aluminium profile. The light stream of the luminaire used is 3000 Colour temperature is 4000 K. Luminaire designed to be suspended from ceiling and suitable for illuminating recreational areas, halls, entrances, shops and shopping malls. This versions with aluminium reflector have UGR<19 so can be used for Lighting offices where an industrial look is defined.

| | |
|---------------------------|--|
| Item code | 0D1STL30AL9 |
| Product type | IN |
| Category | Surface Downlights |
| Family | Saturn |
| Subfamily | Saturn Led |
| Materials | Luminaire lampshade shall be made from aluminium and Luminaire coffer made from aluminium profile. |
| Optical system | Luminaire sets a lampshade made from aluminium. |
| Installation instructions | Luminaire designed to be suspended from the ceiling. |

Pictograms

