


**Dimensions**

Product dimensions (mm)	375 x 250 x 175
-------------------------	-----------------

Scheme**Scheme**

65W	L=388	H=152,5
130W	L=388	H=152,5
198W	L=438	H=182,5

Product

Real power (W)	184
Real luminous flux (Lm)	17903
Luminous efficiency (Lm/W)	97
Beam angle (°)	90
Life time (h)	60000
IP	65
IK	10
Electrical class insulation	Class 1
Operating temperature	from -25°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	Anthracite
Diffuser	Micro-prismatic diffuser

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear

Light source

Light source included	Yes
Light source	Led
Nominal power (W)	184
Nominal luminous flux (Lm)	21570
Average life time (h)	60000
Colour temperature (K)	5700
CRI	70

LED Industrial lowbay luminaire from the TROLL family OKTAN.**DESCRIPTION**

LED Industrial lowbay luminaire from the TROLL family OKTAN. It is a specialized series of LED industrial low-bay fittings. Oktan is an excellent choice for lighting both industrial premises and petrol-stations as well as sports halls.

Item code	0D3OL184NCWSY
Product type	IN
Category	Industrial
Family	Lowbays
Subfamily	Oktan Led
Installation instructions	Luminaire designed to be installed surface mounted on the ceiling
Pictograms	