




---

**Dimensions**


---

Product dimensions (mm) 50 x 574 x 60

---




---

**Scheme**


---

Scheme

---




---

**Product**


---

Real power (W)	9
Real luminous flux (Lm)	1012
Luminous efficiency (Lm/W)	112
Life time (h)	60000
IP	44
IK	4
Electrical class insulation	Class 1
Operating temperature	from 5°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	Anodized aluminum
Diffuser	PMMA opal diffuser

---



---

**Control gear**


---

Control gear included	Yes
Control gear	Electronic Control Gear

---



---

**Light source**


---

Light source included	Yes
Light source	LED
Nominal power (W)	8
Nominal luminous flux (Lm)	1392
Average life time (h)	60000
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80

---



---

**Surface mounted and wall luminaire belonging to TROLL family X-Wall K9 LED.**


---

**DESCRIPTION**

Surface mounted and wall luminaire belonging to TROLL family X-Wall K9 LED. This fixture is recommended for hospital bathrooms and wards. Luminaire body made from aluminium profile. Luminaire set diffuser made from plastic with asymmetric optical system which provides high energetic efficiency.

Item code	0E1XK9L10APLX
Product type	IN
Category	Apliques
Family	X-Line
Subfamily	X-Wall K9 Led
Materials	Luminaire body made from aluminium profile with diffuser made from plastic.
Optical system	Luminaire set a diffuser made from plastic with asymmetric optical system.
Installation instructions	Luminaire designed to be wall surface mounted.

**Pictograms**
