



#### Dimensions

Product dimensions (mm) 1694 x 50 x 60

#### Scheme

#### Scheme



### Surface mounted and wall luminaire belonging to TROLL family X-Wall K9 LED.

#### DESCRIPTION

Surface mounted and wall luminaire belonging to TROLL family X-Wall K9 LED. This fixture is recommended for hospital bathrooms and wards. Luminaire body made from aluminium profile. Luminaire set diffuser made from plastic with asymmetric optical system which provides high energetic efficiency.

Item code	0E1XK9L66APLX
Product type	IN
Category	Apliques
Family	X-Line
Subfamily	X-Wall K9 Led
Materials	Luminaire body made from aluminium profile with diffuser made from plastic.
Optical system	Luminaire set a diffuser made from plastic with asymmetric optical system.
Installation instructions	Luminaire designed to be wall surface mounted.

#### Pictograms



#### Product

Real power (W)	47
Real luminous flux (Lm)	5160
Luminous efficiency (Lm/W)	110
Life time (h)	60000
IP	44
IK	04
Electrical class insulation	Class 1
Operating temperature	from 5°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	Grey
Diffuser	PMMA opal diffuser

#### Control gear

Control gear included	Yes
Control gear	Electronic Control Gear

#### Light source

Light source included	Yes
Light source	Led
Nominal power (W)	37
Nominal luminous flux (Lm)	6966
Average life time (h)	60000
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80