




Dimensions

Product dimensions (mm) 1694 x 50 x 60

Scheme

Scheme



Product

| | |
|-----------------------------|--------------------|
| Real power (W) | 47 |
| Real luminous flux (Lm) | 5160 |
| Luminous efficiency (Lm/W) | 110 |
| Life time (h) | 60000 |
| IP | 44 |
| IK | 04 |
| Electrical class insulation | Class 1 |
| Operating temperature | from 5°C to 30°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | Grey |
| Diffuser | PMMA opal diffuser |

Control gear

| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |

Light source

| | |
|----------------------------|-------|
| Light source included | Yes |
| Light source | LED |
| Nominal power (W) | 37 |
| Nominal luminous flux (Lm) | 6615 |
| Average life time (h) | 60000 |
| Colour temperature (K) | 3000 |
| Colour consistency (SDCM) | 3 |
| CRI | 80 |

Surface mounted and wall luminaire belonging to TROLL family X-Wall K9 LED.

DESCRIPTION

Surface mounted and wall luminaire belonging to TROLL family X-Wall K9 LED. This fixture is recommended for hospital bathrooms and wards. Luminaire body made from aluminium profile. Luminaire set diffuser made from plastic with asymmetric optical system which provides high energetic efficiency.

| | |
|---------------------------|---|
| Item code | 0E1XK9L66BPLX |
| Product type | IN |
| Category | Apliques |
| Family | X-Line |
| Subfamily | X-Wall K9 Led |
| Materials | Luminaire body made from aluminium profile with diffuser made from plastic. |
| Optical system | Luminaire set a diffuser made from plastic with asymmetric optical system. |
| Installation instructions | Luminaire designed to be wall surface mounted. |

Pictograms
