

**Dimensions**

Product dimensions (mm)	63 x 1132 x 74
-------------------------	----------------

**Product**

Real power (W)	32
Real luminous flux (Lm)	3534
Luminous efficiency (Lm/W)	110,44
Beam angle (°)	80
Life time (h)	60000 (L80B10)
IP	44
IK	4
Electrical class insulation	Class 1

Photobiological risk	0 - Exempt
----------------------	------------

Operating temperature	from 5°C to 30°C
-----------------------	------------------

Electrical feeding	220..240V, 50/60Hz
--------------------	--------------------

Colour	Anodized aluminum
--------	-------------------

Energy efficiency class	A++
-------------------------	-----

Diffuser	Micro-prismatic diffuser
----------	--------------------------

**Control gear**

Control gear included	Yes
-----------------------	-----

Control gear	Electronic Control Gear
--------------	-------------------------

**Light source**

Light source included	Yes
-----------------------	-----

Light source	Led
--------------	-----

Nominal power (W)	25
-------------------	----

Nominal luminous flux (Lm)	4644
----------------------------	------

Average life time (h)	60000
-----------------------	-------

Colour temperature (K)	4000
------------------------	------

Colour consistency (SDCM)	3
---------------------------	---

CRI	80
-----	----

**Accessories**

AG6E1-600XLN1P	X-LINE ONE-POINT SUSPENSION WITHOUT CORD 24 LENGTH 1,6M
AG6E1-600XLN1P-3	X-LINE ONE-POINT SUSPENSION WITH THREE-WIRE CORD 24 LENGTH 1,6M
AG6E1-600XLN1P-3W	X-LINE ONE-POINT SUSPENSION WITH THREE-WIRE CORD 34 LENGTH 1,6M
AG6E1-600XLN1PW	X-LINE ONE-POINT SUSPENSION WITHOUT CORD 34 LENGTH 1,6M

**1200 mm length LED linear surface mounted or hanging luminaire for single use from the TROLL family X-Line.****DESCRIPTION**

Type of product - for indoor uses. The way of mounting - surface mounted on slings or directly mounted to ceiling construction. Luminaire housing made of aluminum profile. Housing colour - anodised aluminum. Luminaire dimensions: length - 1132 mm, width - 63 mm, height - 74 mm. Optical system - micro prism diffuser made of polycarbonate. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 4712 lm. LED sources power - 29,6 W. Colour temperature of light source - 4000K. SDCM=3. CRI780. Durability of LED light sources - 60000 h (L80/B10). Luminous flux of the luminaire - 3534 lm. Power consumed by the luminaire - 32 W. Luminous efficacy of the luminaire - 110,44 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP44. Protection level IK - IK04. Protection against electric shock - class I. Certificates and admissions - CE. Accessories: slings.

Item code	0E1XLL40AMIC
Product type	IN
Category	Surface Linears
Family	X-Line
Subfamily	X-Line Led
Materials	Luminaire housing made of aluminum profile.
Optical system	Optical system - micro prism diffuser made of polycarbonate.
Installation instructions	The way of mounting - surface mounted on slings or directly mounted to ceiling construction.