




## Dimensions

Product dimensions (mm) 63 x 1407 x 74

## Scheme

## Scheme






2680 / L=1200 C=1127 D=1122 E=3376 F=1000 h=1000 J=122 K=66  
4480 / L=1200 C=1127 D=1122 E=3376 F=1000 h=1000 J=122 K=66  
3250 / L=1500 C=1407 D=1482 E=4216 F=1200 h=1200 J=202 K=106  
3580 / L=1500 C=1407 D=1482 E=4216 F=1200 h=1200 J=202 K=106  
3900 / L=1700 C=1687 D=1682 E=5056 F=1500 h=1500 J=182 K=76  
3900 / L=1700 C=1687 D=1682 E=5056 F=1500 h=1500 J=182 K=76

## 1500 mm length LED linear surface mounted or hanging luminaire for continuous line use from the TROLL family X-Line.

## DESCRIPTION

Type of product - for indoor uses. The way of mounting - surface mounted on slings or directly mounted to ceiling construction. Luminaire housing made of aluminum profile. Housing colour - anodised aluminum. Luminaire dimensions: length - 1407 mm, width - 63 mm, height - 74 mm. Optical system - micro prism diffuser made of polycarbonate. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 3385 lm. LED sources power - 21 W. Colour temperature of light source - 4000K. SDCM=3. CRI780. Durability of LED light sources - 60000 h (L80/B10). Luminous flux of the luminaire - 2538 lm. Power consumed by the luminaire - 23 W. Luminous efficacy of the luminaire - 110,35 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP44. Protection level IK - IK04. Protection against electric shock - class I. Certificates and admissions - CE. Additional information: luminaire to be mounted in the line, left element, three-circuit. Accessories: slings, cross connectors, line connector.

|                           |   |
|---------------------------|---|
| Item code                 | 0E1XLLA325AMIC  |
| Product type              | IN  |
| Category                  | Surface Linears   |
| Family                    | X-Line  |
| Subfamily                 | X-Line Led  |
| Materials                 | Luminaire housing made of aluminum profile.   |
| Optical system            | Optical system - micro prism diffuser made of polycarbonate.  |
| Installation instructions | The way of mounting - surface mounted on slings or directly mounted to ceiling construction.  |
| Pictograms                |    |

## Product

|                            |                |
|----------------------------|----------------|
| Real power (W)             | 23             |
| Real luminous flux (Lm)    | 2538           |
| Luminous efficiency (Lm/W) | 110,35         |
| Beam angle (°)             | 80             |
| Life time (h)              | 60000 (L80B10) |
| IP                         | 44             |
| IK                         | 4              |

|                             |                          |
|-----------------------------|--------------------------|
| Electrical class insulation | Class 1                  |
| Photobiological risk        | 0 - Exempt               |
| Operating temperature       | from 5°C to 30°C         |
| Electrical feeding          | 220..240V, 50/60Hz       |
| Colour                      | Anodized aluminum        |
| Energy efficiency class     | A++                      |
| Diffuser                    | Micro-prismatic diffuser |

## Control gear

|                       |                         |
|-----------------------|-------------------------|
| Control gear included | Yes                     |
| Control gear          | Electronic Control Gear |

## Light source

|                            |       |
|----------------------------|-------|
| Light source included      | Yes   |
| Light source               | Led   |
| Nominal power (W)          | 19    |
| Nominal luminous flux (Lm) | 3550  |
| Average life time (h)      | 60000 |
| Colour temperature (K)     | 4000  |
| Colour consistency (SDCM)  | 3     |
| CRI                        | 80    |

| Accessories       |  |
|-------------------|--|
| AG0E1XLL-SLED     | X-LINE LUMINAIRES CONNECTORLED                                   |
| AG6E1-600XLN1P    | X-LINE ONE-POINT SUSPENSIONWITHOUT CORD 24<br>LENGTH 1,6M        |
| AG6E1-600XLN1P-3  | X-LINE ONE-POINT SUSPENSIONWITH THREE-WIRE CORD<br>24LENGTH 1,6M |
| AG6E1-600XLN1P-3W | X-LINE ONE-POINT SUSPENSIONWITH THREE-WIRE<br>CORD 34LENGTH 1,6M |
| AG6E1-600XLN1PW   | X-LINE ONE-POINT SUSPENSIONWITHOUT CORD 34<br>LENGTH 1,6M        |