




Dimensions

Product dimensions (mm) 63 x 1687 x 74

Scheme

Scheme



| | | | | | | | |
|---------------|--------|--------|--------|--------|--------|--------|-------|
| 2680 / L=1200 | C=1127 | D=1122 | E=3376 | F=1000 | H=1000 | J=1122 | K=66 |
| 4480 / L=1200 | C=1127 | D=1122 | E=3376 | F=1000 | H=1000 | J=1122 | K=66 |
| 3250 / L=1500 | C=1407 | D=1402 | E=4216 | F=1200 | H=1200 | J=1202 | K=106 |
| 3980 / L=1500 | C=1407 | D=1402 | E=4216 | F=1200 | H=1200 | J=1202 | K=106 |
| 3980 / L=1700 | C=1687 | D=1682 | E=5056 | F=1500 | H=1500 | J=1682 | K=96 |
| 3980 / L=1700 | C=1687 | D=1682 | E=5056 | F=1500 | H=1500 | J=1682 | K=96 |

1700 mm length LED linear surface mounted or hanging luminaire for continuous line use from the TROLL family X-Line.

DESCRIPTION

Type of product - for indoor uses. The way of mounting - surface mounted on slings or directly mounted to ceiling construction. Luminaire housing made of aluminum profile. Housing colour - anodised aluminum. Luminaire dimensions: length - 1687 mm, width - 63 mm, height - 74 mm. Optical system - micro prism diffuser made of polycarbonate. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 7068 lm. LED sources power - 44,4 W. Colour temperature of light source - 4000K. SDCM=3. CRI>80. Durability of LED light sources - 60000 h (L80/B10). Luminous efficacy of the luminaire - 5301 lm. Power consumed by the luminaire - 47 W. Luminous efficacy of the luminaire - 112,79 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP44. Protection level IK - IK04. Protection against electric shock - class I. Certificates and admissions - CE. Additional information: luminaire to be mounted in the line, right element, three-circuit. Accessories: slings, cross connectors, line connector.

| | |
|---------------------------|--|
| Item code | 0E1XLLC60BMICO |
| Product type | IN |
| Category | Surface Linears |
| Family | X-Line |
| Subfamily | X-Line Led |
| Materials | Luminaire housing made of aluminum profile. |
| Optical system | Optical system - micro prism diffuser made of polycarbonate. |
| Installation instructions | The way of mounting - surface mounted on slings or directly mounted to ceiling construction. |

Pictograms



Product

| | |
|-----------------------------|--------------------------|
| Real power (W) | 47 |
| Real luminous flux (Lm) | 5301 |
| Luminous efficiency (Lm/W) | 112,79 |
| Beam angle (°) | 80 |
| Life time (h) | 60000 (L80B10) |
| IP | 44 |
| IK | 4 |
| Electrical class insulation | Class 1 |
| Photobiological risk | 0 - Exempt |
| Operating temperature | from 5°C to 30°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | Anodized aluminum |
| Energy efficiency class | A++ |
| Diffuser | Micro-prismatic diffuser |

Control gear

| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |

Light source

| | |
|----------------------------|-------|
| Light source included | Yes |
| Light source | LED |
| Nominal power (W) | 37 |
| Nominal luminous flux (Lm) | 6966 |
| Average life time (h) | 60000 |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | 3 |
| CRI | 80 |

Accessories

AG0E1XLL-SLED X-LINE LUMINAIRES CONNECTORLED

AG6E1- X-LINE ONE-POINT SUSPENSIONWITHOUT CORD 24
600XLN1P LENGTH 1,6M

AG6E1- X-LINE ONE-POINT SUSPENSIONWITH THREE-WIRE CORD
600XLN1P-3 24LENGTH 1,6M

AG6E1- X-LINE ONE-POINT SUSPENSIONWITH THREE-WIRE
600XLN1P-3W CORD 34LENGTH 1,6M

AG6E1- X-LINE ONE-POINT SUSPENSIONWITHOUT CORD 34
600XLN1PW LENGTH 1,6M