


**Dimensions**

Product dimensions (mm)	80 x 1122 x 136
Drilling hole (mm)	70 x 1222

**Scheme****Scheme****Product**

Real power (W)	18
Real luminous flux (Lm)	2088
Luminous efficiency (Lm/W)	116,00
Beam angle (°)	80
Life time (h)	60000 (L80B10)
IP	44
IK	4
Electrical class insulation	Class 1
Photobiological risk	0 - Exempt
Operating temperature	from 5°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	Anodized aluminum
Energy efficiency class	A++
Diffuser	Micro-prismatic diffuser

**Control gear**

Control gear included	Yes
Control gear	Electronic Control Gear

**Light source**

Light source included	Yes
Light source	Led
Nominal power (W)	15
Nominal luminous flux (Lm)	2840
Average life time (h)	60000
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80

**Accessories**

AG0E1XLL-SLED	X-LINE LUMAIRES CONNECTOR LED
---------------	-------------------------------

**1200 mm length LED linear recessed luminaire for continuous line use from the TROLL family X-Line.****DESCRIPTION**

Type of product - for indoor uses. The way of mounting - recessed in suspended ceiling. Luminaire housing made of aluminum profile. Housing colour - anodised aluminum. Luminaire dimensions: length - 1122 mm, width - 80 mm, height - 136 mm. Optical system - micro prism diffuser made of polycarbonate. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 2784 lm. LED sources power - 17,4 W. Colour temperature of light source - 4000K, SDCM=3. CRI?80. Durability of LED light sources - 60000 h (L80/B10). Luminous flux of the luminaire - 2088 lm. Power consumed by the luminaire - 18 W. Luminous efficacy of the luminaire - 116,00 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP44. Protection level IK - IK04. Protection against electric shock - class I. Certificates and admissions - CE. Additional information: luminaire to be mounted in the line, middle element, three-circuit. Accessories: cross connectors, line connector.

Item code	0E1XLLCG26AMIC
Product type	IN
Category	Recessed Linears
Family	X-Line
Subfamily	X-Line G/K Led
Materials	Luminaire housing made of aluminum profile.
Optical system	Optical system - micro prism diffuser made of polycarbonate.
Installation instructions	The way of mounting - recessed in suspended ceiling.
Pictograms	