




#### Dimensions

Product dimensions (mm)	80 x 1422 x 136
Drilling hole (mm)	70 X 1412

#### Scheme

#### Scheme



2600 lm / L=1200	A=1142 - D=1125
4400 lm / L=1200	A=1142 - D=1125
3250 lm / L=1500	A=1422 - D=1405
5500 lm / L=1500	A=1422 - D=1405
3900 lm / L=1700	A=1702 - D=1685
6600 lm / L=1700	A=1702 - D=1685

### 1500 mm length LED linear recessed luminaire for single use from the TROLL family X-Line.

#### DESCRIPTION

Type of product - for indoor uses. The way of mounting - recessed in suspended ceiling. Mounting hole - 1412x80 mm. Luminaire housing made of aluminum profile. Housing colour - anodised aluminum. Luminaire dimensions: length - 1422 mm, width - 80 mm, height - 136 mm. Optical system - micro prism diffuser made of polycarbonate. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 3385 lm. LED sources power - 21 W. Colour temperature of light source - 4000K. SDCM=3. CRI?80. Durability of LED light sources - 60000 h (L80/B10). Luminous flux of the luminaire - 2538 lm. Power consumed by the luminaire - 23 W. Luminous efficacy of the luminaire - 110,35 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP44. Protection level IK - IK04. Protection against electric shock - class I. Certificates and admissions - CE.

Item code	0E1XLLG325AMIC
Product type	IN
Category	Recessed Linears
Family	X-Line
Subfamily	X-Line G/K Led
Materials	Luminaire housing made of aluminum profile.
Optical system	Optical system - micro prism diffuser made of polycarbonate.
Installation instructions	The way of mounting - recessed in suspended ceiling.

#### Pictograms



#### Product

Real power (W)	23
Real luminous flux (Lm)	2538
Luminous efficiency (Lm/W)	110,35
Beam angle (°)	80
Life time (h)	60000 (L80B10)
IP	44
IK	4
Electrical class insulation	Class 1
Photobiological risk	0 - Exempt
Operating temperature	from 5°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	Anodized aluminum
Energy efficiency class	A++
Diffuser	Micro-prismatic diffuser

#### Control gear

Control gear included	Yes
Control gear	Electronic Control Gear

#### Light source

Light source included	Yes
Light source	Led
Nominal power (W)	19
Nominal luminous flux (Lm)	3550
Average life time (h)	60000
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80