


## Dimensions

|                         |                  |
|-------------------------|------------------|
| Product dimensions (mm) | 1047 x 2034 x 72 |
|-------------------------|------------------|

## Scheme

## Scheme



## Product

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 36                 |
| Real luminous flux (Lm)     | 3953               |
| Luminous efficiency (Lm/W)  | 109,81             |
| Beam angle (°)              | 95                 |
| Life time (h)               | 60000 (L80B10)     |
| IP                          | 20                 |
| IK                          | 2                  |
| Electrical class insulation | Class 1            |
| Photobiological risk        | 0 - Exempt         |
| Operating temperature       | from 5°C to 30°C   |
| Electrical feeding          | 220..240V, 50/60Hz |
| Colour                      | Anodized aluminum  |
| Energy efficiency class     | B                  |
| Diffuser                    | PMMA opal diffuser |

## Control gear

|                       |                         |
|-----------------------|-------------------------|
| Control gear included | Yes                     |
| Control gear          | Electronic Control Gear |

## Light source

|                            |       |
|----------------------------|-------|
| Light source included      | Yes   |
| Light source               | Led   |
| Nominal power (W)          | 30    |
| Nominal luminous flux (Lm) | 5680  |
| Average life time (h)      | 60000 |
| Colour temperature (K)     | 4000  |
| Colour consistency (SDCM)  | 3     |
| CRI                        | 80    |

## Accessories

|                   |   |
|-------------------|---|
| AG6E1-600XLNIP    | X-LINE ONE-POINT SUSPENSION WITHOUT CORD 24 LENGTH 1,6M         |
| AG6E1-600XLNIP-3  | X-LINE ONE-POINT SUSPENSION WITH THREE-WIRE CORD 24 LENGTH 1,6M |
| AG6E1-600XLNIP-3W | X-LINE ONE-POINT SUSPENSION WITH THREE-WIRE CORD 34 LENGTH 1,6M |
| AG6E1-600XLNIPW   | X-LINE ONE-POINT SUSPENSION WITHOUT CORD 34 LENGTH 1,6M         |

## Architectural LED linear luminaire from the TROLL family X-Line Snake.

## DESCRIPTION

Type of product - for indoor uses. The way of mounting - surface mounted or on slings. Luminaire housing made of aluminum profile. Luminaire dimensions: length - 2034 mm, width - 1047 mm, height - 72 mm. Optical system - PMMA opalized diffuser. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 5416 lm. LED sources power - 30 W. Colour temperature of light source - 4000K. SDCM=3. CRI>80. Durability of LED light sources - 60000 h (L80/B10). Luminous flux of the luminaire - 3953 lm. Power consumed by the luminaire - 36 W. Luminous efficacy of the luminaire - 109,81 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP20. Protection level IK - IK02. Protection against electric shock - class I. Certificates and admissions - CE. Accessories: slings.

|                           |   |
|---------------------------|---|
| Item code                 | 0E1XSVL52APLX                                       |
| Product type              | IN  |
| Category                  | Surface Linears                                     |
| Family                    | X-Line  |
| Subfamily                 | Snake Led   |
| Materials                 | Luminaire housing made of aluminum profile.         |
| Optical system            | Optical system - PMMA opalized diffuser.            |
| Installation instructions | The way of mounting - surface mounted or on slings. |

## Pictograms

