


Dimensions

Product dimensions (mm) 1047 x 2034 x 72

Scheme

Scheme



Product

| | |
|-----------------------------|--------------------|
| Real power (W) | 36 |
| Real luminous flux (Lm) | 3953 |
| Luminous efficiency (Lm/W) | 109,81 |
| Beam angle (°) | 95 |
| Life time (h) | 60000 (L80B10) |
| IP | 20 |
| IK | 2 |
| Electrical class insulation | Class 1 |
| Photobiological risk | 0 - Exempt |
| Operating temperature | from 5°C to 30°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | Anodized aluminum |
| Energy efficiency class | B |
| Diffuser | PMMA opal diffuser |

Control gear

| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |

Light source

| | |
|----------------------------|-------|
| Light source included | Yes |
| Light source | Led |
| Nominal power (W) | 30 |
| Nominal luminous flux (Lm) | 5680 |
| Average life time (h) | 60000 |
| Colour temperature (K) | 4000 |
| Colour consistency (SDCM) | 3 |
| CRI | 80 |

Accessories

| | |
|-------------------|-----------------------------------------------------------------|
| AG6E1-600XLNIP | X-LINE ONE-POINT SUSPENSION WITHOUT CORD 24 LENGTH 1,6M |
| AG6E1-600XLNIP-3 | X-LINE ONE-POINT SUSPENSION WITH THREE-WIRE CORD 24 LENGTH 1,6M |
| AG6E1-600XLNIP-3W | X-LINE ONE-POINT SUSPENSION WITH THREE-WIRE CORD 34 LENGTH 1,6M |
| AG6E1-600XLNIPW | X-LINE ONE-POINT SUSPENSION WITHOUT CORD 34 LENGTH 1,6M |

Architectural LED linear luminaire from the TROLL family X-Line Snake.

DESCRIPTION

Type of product - for indoor uses. The way of mounting - surface mounted or on slings. Luminaire housing made of aluminum profile. Luminaire dimensions: length - 2034 mm, width - 1047 mm, height - 72 mm. Optical system - PMMA opalized diffuser. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 5416 lm. LED sources power - 30 W. Colour temperature of light source - 4000K. SDCM=3. CRI>80. Durability of LED light sources - 60000 h (L80/B10). Luminous flux of the luminaire - 3953 lm. Power consumed by the luminaire - 36 W. Luminous efficacy of the luminaire - 109,81 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP20. Protection level IK - IK02. Protection against electric shock - class I. Certificates and admissions - CE. Accessories: slings.

| | |
|---------------------------|-----------------------------------------------------|
| Item code | 0E1XSVL52APLX |
| Product type | IN |
| Category | Surface Linears |
| Family | X-Line |
| Subfamily | Snake Led |
| Materials | Luminaire housing made of aluminum profile. |
| Optical system | Optical system - PMMA opalized diffuser. |
| Installation instructions | The way of mounting - surface mounted or on slings. |

Pictograms

