



Dimensions	
------------	--

Product dimensions (mm)	1047 x 2034 x 72
-------------------------	------------------

Scheme	
--------	--

Scheme	
--------	--



Product	
---------	--

Real power (W)	36
Real luminous flux (Lm)	3962
Luminous efficiency (Lm/W)	110
Beam angle (°)	95
Life time (h)	60000 (L80B10)
IP	20
IK	2
Electrical class insulation	Class 1
Photobiological risk	0 - Exempt
Operating temperature	from 5°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	White
Energy efficiency class	A++
Diffuser	Micro-prismatic diffuser

Control gear	
--------------	--

Control gear included	Yes
Control gear	Electronic Control Gear

Light source	
--------------	--

Light source included	Yes
Light source	Led
Nominal power (W)	30
Nominal luminous flux (Lm)	5080
Average life time (h)	60000
Colour temperature (K)	3000
Colour consistency (SDCM)	3
CRI	80

Accessories	
-------------	--

AG6E1-600XLNIP-3W	X-LINE ONE-POINT SUSPENSION WITH THREE-WIRE CORD 34 LENGTH 1,6M
AG6E1-600XLNIPW	X-LINE ONE-POINT SUSPENSION WITHOUT CORD 34 LENGTH 1,6M

Architectural LED linear luminaire from the TROLL family X-Line Snake.

DESCRIPTION

Type of product - for indoor uses. The way of mounting - surface mounted or on slings. Luminaire housing made of aluminum profile. Housing colour - white (RAL 9016). Luminaire dimensions: length - 2034 mm, width - 1047 mm, height - 72 mm. Optical system - micro prism diffuser made of polycarbonate. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 5416 lm. LED sources power - 30 W. Colour temperature of light source - 3000K, SDCM=3, CRI>80. Durability of LED light sources - 60000 h (L80/B10). Luminous flux of the luminaire - 3962 lm. Power consumed by the luminaire - 36 W. Luminous efficacy of the luminaire - 110 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP20. Protection level IK - IK02. Protection against electric shock - class I. Certificates and admissions - CE. Accessories: slings.

Item code	0E1XSVL52BMPRW
Product type	IN
Category	Surface Linears
Family	X-Line
Subfamily	Snake Led
Materials	Luminaire housing made of aluminum profile.
Optical system	Optical system - micro prism diffuser made of polycarbonate.
Installation instructions	The way of mounting - surface mounted or on slings.

Pictograms

