




---

**Dimensions**


---

|                         |                  |
|-------------------------|------------------|
| Product dimensions (mm) | 1047 x 2034 x 72 |
|-------------------------|------------------|

---



---

**Scheme**


---



---

**Scheme**


---




---

**Product**


---

|                             |                          |
|-----------------------------|--------------------------|
| Real power (W)              | 62                       |
| Real luminous flux (Lm)     | 7188                     |
| Luminous efficiency (Lm/W)  | 116                      |
| Beam angle (°)              | 95                       |
| Life time (h)               | 60000 (L80B10)           |
| IP                          | 20                       |
| IK                          | 2                        |
| Electrical class insulation | Class 1                  |
| Photobiological risk        | 0 - Exempt               |
| Operating temperature       | from 5°C to 30°C         |
| Electrical feeding          | 220..240V, 50/60Hz       |
| Colour                      | Anodized aluminum        |
| Energy efficiency class     | A++                      |
| Diffuser                    | Micro-prismatic diffuser |

---



---

**Control gear**


---

|                       |                         |
|-----------------------|-------------------------|
| Control gear included | Yes                     |
| Control gear          | Electronic Control Gear |

---



---

**Light source**


---

|                            |       |
|----------------------------|-------|
| Light source included      | Yes   |
| Light source               | LED   |
| Nominal power (W)          | 50    |
| Nominal luminous flux (Lm) | 9288  |
| Average life time (h)      | 60000 |
| Colour temperature (K)     | 4000  |
| Colour consistency (SDCM)  | 3     |
| CRI                        | 80    |

---



---

**Accessories**


---

|                   |   |
|-------------------|---|
| AG6E1-600XLNIP-3W | X-LINE ONE-POINT SUSPENSION WITH THREE-WIRE CORD 34 LENGTH 1,6M |
| AG6E1-600XLNIPW   | X-LINE ONE-POINT SUSPENSION WITHOUT CORD 34 LENGTH 1,6M         |

---



---

**Architectural LED linear luminaire from the TROLL family X-Line Snake.**


---






---

**DESCRIPTION**


---

Type of product - for indoor uses. The way of mounting - surface mounted or on slings. Luminaire housing made of aluminum profile. Luminaire dimensions: length - 2034 mm, width - 1047 mm, height - 72 mm. Optical system - micro prism diffuser made of polycarbonate. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 9216 lm. LED sources power - 50 W. Colour temperature of light source - 4000K. SDCM=3. CRI>80. Durability of LED light sources - 60000 h (L80/B10). Luminous flux of the luminaire - 7188 lm. Power consumed by the luminaire - 62 W. Luminous efficacy of the luminaire - 116 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP20. Protection level IK - IK02. Protection against electric shock - class I. Certificates and admissions - CE. Accessories: slings.

---

|                           |   |
|---------------------------|---|
| Item code                 | 0E1XSVL88AMPR   |
| Product type              | IN  |
| Category                  | Surface Linears   |
| Family                    | X-Line  |
| Subfamily                 | Snake Led   |
| Materials                 | Luminaire housing made of aluminum profile.   |
| Optical system            | Optical system - micro prism diffuser made of polycarbonate.  |
| Installation instructions | The way of mounting - surface mounted or on slings.   |
| Pictograms                |    |

---