



Dimensions

Product dimensions (mm)	1047 x 2034 x 72
-------------------------	------------------

Scheme

Scheme



Product

Real power (W)	62
Real luminous flux (Lm)	7188
Luminous efficiency (Lm/W)	116
Beam angle (°)	95
Life time (h)	60000 (L80B10)
IP	20
IK	2
Electrical class insulation	Class 1
Photobiological risk	0 - Exempt
Operating temperature	from 5°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	White
Energy efficiency class	A++
Diffuser	Micro-prismatic diffuser

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear

Light source

Light source included	Yes
Light source	LED
Nominal power (W)	50
Nominal luminous flux (Lm)	9288
Average life time (h)	60000
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80

Accessories

AG6E1-600XLNIP-3W	X-LINE ONE-POINT SUSPENSION WITH THREE-WIRE CORD 34 LENGTH 1,6M
AG6E1-600XLNIPW	X-LINE ONE-POINT SUSPENSION WITHOUT CORD 34 LENGTH 1,6M

Architectural LED linear luminaire from the TROLL family X-Line Snake.

DESCRIPTION

Type of product - for indoor uses. The way of mounting - surface mounted or on slings. Luminaire housing made of aluminum profile. Housing colour - white (RAL 9016). Luminaire dimensions: length - 2034 mm, width - 1047 mm, height - 72 mm. Optical system - micro prism diffuser made of polycarbonate. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 9216 lm. LED sources power - 50 W. Colour temperature of light source - 4000K, SDCM=3, CRI>80. Durability of LED light sources - 60000 h (L80/B10). Luminous flux of the luminaire - 7188 lm. Power consumed by the luminaire - 62 W. Luminous efficacy of the luminaire - 116 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP20. Protection level IK - IK02. Protection against electric shock - class I. Certificates and admissions - CE. Accessories: slings.

Item code	0E1XSVL88AMPRW
Product type	IN
Category	Surface Linears
Family	X-Line
Subfamily	Snake Led
Materials	Luminaire housing made of aluminum profile.
Optical system	Optical system - micro prism diffuser made of polycarbonate.
Installation instructions	The way of mounting - surface mounted or on slings.

Pictograms
