


## Dimensions

Product dimensions (mm) 1047 x 2034 x 72

## Scheme

## Scheme



## Product

Real power (W)	62
Real luminous flux (Lm)	6870
Luminous efficiency (Lm/W)	111
Beam angle (°)	95
Life time (h)	60000 (L80B10)
IP	20
IK	2
Electrical class insulation	Class 1
Photobiological risk	0 - Exempt
Operating temperature	from 5°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	White
Energy efficiency class	A++
Diffuser	Micro-prismatic diffuser

## Control gear

Control gear included	Yes
Control gear	Electronic Control Gear

## Light source

Light source included	Yes
Light source	Led
Nominal power (W)	50
Nominal luminous flux (Lm)	8804
Average life time (h)	60000
Colour temperature (K)	3000
Colour consistency (SDCM)	3
CRI	80

## Accessories

AG6E1-600XLNIP-3W	X-LINE ONE-POINT SUSPENSION WITH THREE-WIRE CORD 34 LENGTH 1,6M
AG6E1-600XLN1PW	X-LINE ONE-POINT SUSPENSION WITHOUT CORD 34 LENGTH 1,6M

## Architectural LED linear luminaire from the TROLL family X-Line Snake.

## DESCRIPTION

Type of product - for indoor uses. The way of mounting - surface mounted or on slings. Luminaire housing made of aluminum profile. Housing colour - white (RAL 9016). Luminaire dimensions: length - 2034 mm, width - 1047 mm, height - 72 mm. Optical system - micro prism diffuser made of polycarbonate. Luminaire is equipped with light source. Types of light sources - LED. Printed circuit board for mounting LED made of aluminum. Luminous flux of LED sources - 8804 lm. LED sources power - 50 W. Colour temperature of light source - 3000K, SDCM=3. CRI>80. Durability of LED light sources - 60000 h (L80/B10). Luminous flux of the luminaire - 6870 lm. Power consumed by the luminaire - 62 W. Luminous efficacy of the luminaire - 111 lm/W. Type of power supply - electronic gear. Operational temperature range of the luminaire 5°C to 30°C. Protection level IP - IP20. Protection level IK - IK02. Protection against electric shock - class I. Certificates and admissions - CE. Accessories: slings.

Item code	0E1XSVL88BMPRW
Product type	IN
Category	Surface Linears
Family	X-Line
Subfamily	Snake Led
Materials	Luminaire housing made of aluminum profile.
Optical system	Optical system - micro prism diffuser made of polycarbonate.
Installation instructions	The way of mounting - surface mounted or on slings.
Pictograms	