


Dimensions

Scheme

Scheme



Product

Real power (W)	2 x 1,9
Real luminous flux (Lm)	214
Luminous efficiency (Lm/W)	58
Beam angle (°)	2 x (9 x 36)
Life time (h)	50000
IP	20
IK	04
Electrical class insulation	Class 1
Operating temperature	from 5°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	Grey

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear

Light source

Light source included	Yes
Light source	LED
Nominal power (W)	3,4
Nominal luminous flux (Lm)	304
Average life time (h)	50000
Colour temperature (K)	3000
Diameter (mm)	50000
Colour consistency (SDCM)	5
CRI	80
TM30RF	80

Decorative sconce from the TROLL family Mini wall C Led.

DESCRIPTION

Decorative sconce from the TROLL family Mini wall C Led. Luminaire made from Aluminium with lenses of renowned producers which allows unlimited possibilities to arrange luminous flux up and down. MINI WALL C LED is recommended to be installed as a decorative and accent Lighting in both indoor and outdoor façades.

Item code	0KFL21-2
Product type	IN
Category	Apliques
Family	Mini Wall
Subfamily	Mini Wall Led
Materials	Luminaire body made of aluminium with plastic lenses.
Optical system	The fixture sets an optical system based on lenses which produce a double beam 9° x 36°.
Installation instructions	Luminaire designed to be wall surface mounted.

Pictograms

