




---

**Dimensions**


---

Product dimensions (mm)	45 x 45 x 120
Net weight (g)	300

---




---

**Scheme**


---

Scheme




---

**Product**


---

Real power (W)	1,7
Real luminous flux (Lm)	96
U.G.R. (%)	< 19
Luminous efficiency (Lm/W)	56
Life time (h)	60000
IP	40
IK	04
Electrical class insulation	Class 1
Operating temperature	from 5°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	Grey

---



---

**Control gear**


---

Control gear included	Yes
Control gear	Electronic Control Gear

---



---

**Light source**


---

Light source included	Yes
Light source	Led
Nominal power (W)	1
Nominal luminous flux (Lm)	87
Average life time (h)	83000
Colour temperature (K)	3000
Colour consistency (SDCM)	5
CRI	80

---



---

**Decorative Luminaire from the TROLL family Beryl KN LED.**


---

**DESCRIPTION**

Decorative Luminaire from the TROLL family Beryl KN LED with 1,5 W, and IP40 dust and water protection class. It is made from powder coated aluminium (RAL9006 standard). Optical system based on Led lenses with different possible light distribution. The standard light distribution is achieved owing to  $\pm 5^\circ \times \pm 21^\circ$  lens. It is also possible to use the symmetric light distribution of 45°. Luminary designed for accent and decorative illumination in such areas as restaurants, pubs, or cafés.

Item code	0KP1-2LED-21
Product type	IN
Category	Apliques
Family	Beryl Kn
Subfamily	Beryl KN Led
Materials	Body made from powder coated aluminium (RAL9006 standard).
Optical system	Optical system based on Led lenses with different possible light distribution.
Installation instructions	Designed to be surface mounted on ceiling.

## Pictograms

