## Item code 0KP1-2LED-21





## Decorative Luminaire from the TROLL family Beryl KN LED.

## DESCRIPTION

Decorative Luminaire from the TROLL family Beryl KN LED with 1,5 W, and IP40 dust and water protection class. It is made from powder coated aluminium (RAL9006 standard). Optical system based on Led lenses with different possible light distribution. The standard light distribution is achieved owing to  $\pm 5^{\circ}$ x $\pm 21^{\circ}$  lens. It is also possible to use the symmetric light distribution of 45°. Luminary designed for accent and decorative illumination in such areas as restaurants, pubs, or cafés.

Item code	0KP1-2LED-21
Product type	IN
Category	Apliques
Family	Beryl Kn
Subfamily	Beryl KN Led
Materials	Body made from powder coated aluminium (RAL9006 standard).
Optical system	Optical system based on Led lenses with different possible light distribution.
Installation instructions	Designed to be surface mounted on ceiling.
Pictograms	






Dimensions		
Product dimensions (mm)	45 x 45 x 120	
Net weight (g)	300	

Scheme

Scheme

Control gear



Product		
Real power (W)	1,7	
Real luminous flux (Lm)	96	
U.G.R. (%)	< 19	
Luminous efficiency (Lm/W)	56	
Life time (h)	60000	
IP	40	
IK	04	
Electrical class insulation	Class 1	
Operating temperature	from 5°C to 30°C	
Electrical feeding	220240V, 50/60Hz	
Colour	Grev	

Control gear included	Yes
Control gear	Electronic Control Gear
Light source	
Light source included	Yes
Light source	Led
Nominal power (W)	1
Nominal luminous flux (Lm)	87
Average life time (h)	83000
Colour temperature (K)	3000
Colour consistency (SDCM)	5
CRI	80