




Dimensions

| | |
|-------------------------|---------------|
| Product dimensions (mm) | 45 x 90 x 160 |
| Net weight (g) | 400 |

Scheme

Scheme



Product

| | |
|-----------------------------|--------------------|
| Real power (W) | 2 x 1,7 |
| Real luminous flux (Lm) | 192 |
| Luminous efficiency (Lm/W) | 56 |
| Beam angle (°) | 2 x (5 x 21) |
| Life time (h) | 50000 |
| IP | 65 |
| IK | 04 |
| Electrical class insulation | Class 1 |
| Operating temperature | from -20°C to 30°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | Grey |

Control gear

| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |


Light source

| | |
|----------------------------|-------|
| Light source included | Yes |
| Light source | Led |
| Nominal power (W) | 1,2 |
| Nominal luminous flux (Lm) | 87 |
| Average life time (h) | 50000 |
| Colour temperature (K) | 6000 |
| Colour consistency (SDCM) | 5 |
| CRI | 80 |

Decorative outdoor sconce from the TROLL family Beryl KN Up and Down.

DESCRIPTION

Decorative outdoor sconce from the TROLL family Beryl KN Up and Down. Luminaire adapted to be mounted on walls setting a high lighting efficiency LEDs were used as light sources. Optical system consists of professional lens that provide elliptical light distribution of 5° x 21° angle beam. Owing to the optical system solutions, the product is highly effective. Its body is made from anodized aluminium profile painted in grey. It is resistant to solids, dust, and liquids penetration IP65. This type of luminaire is recommended for decorative or accent illumination, e.g. in restaurants, pubs, or cafes.

| | |
|---------------------------|--|
| Item code | 0KPGD2-4LED21W |
| Product type | OUT |
| Category | Surface |
| Family | Beryl Kn |
| Subfamily | Beryl KN Led U&D |
| Materials | Luminaire body made from anodized aluminium profile painted in grey. |
| Optical system | Optical system consists of professional lens that provide elliptical light distribution of 5° x 21° angle beam |
| Installation instructions | Luminaire designed to be wall surface mounted. |
| Pictograms |  |