


**Dimensions**

Product dimensions (mm)	45 x 90 x 160
Net weight (g)	400

**Scheme**

Scheme

**Product**

Real power (W)	2 x 1,7
Real luminous flux (Lm)	192
Luminous efficiency (Lm/W)	56
Beam angle (°)	2 x (5 x 21)
Life time (h)	50000
IP	65
IK	04
Electrical class insulation	Class 1
Operating temperature	from -20°C to 30°C
Electrical feeding	220..240V, 50/60Hz
Colour	White

**Control gear**

Control gear included	Yes
Control gear	Electronic Control Gear

**Light source**

Light source included	Yes
Light source	Led
Nominal power (W)	3
Nominal luminous flux (Lm)	248
Average life time (h)	50000
Colour temperature (K)	3000
Colour consistency (SDCM)	5
CRI	80

**Decorative outdoor sconce from the TROLL family Beryl KN Up and Down.****DESCRIPTION**

Decorative outdoor sconce from the TROLL family Beryl KN Up and Down. Luminary adapted to be mounted on walls setting a high lighting efficiency LEDs were used as light sources. Optical system consists of professional lens that provide elliptical light distribution of 5° x 21° angle beam. Owing to the optical system solutions, the product is highly effective. Its body is made from anodized aluminium profile painted in white. It is resistant to solids, dust, and liquids penetration IP65. This type of luminary is recommended for decorative or accent illumination, e.g. in restaurants, pubs, or cafes.

Item code	0KPGD2-4LED34C
Product type	OUT
Category	Surface
Family	Beryl Kn
Subfamily	Beryl KN Led U&D
Materials	Luminaire body made from anodized aluminium profile painted in white.
Optical system	Optical system consists of professional lens that provide elliptical light distribution of 5° x 21° angle beam
Installation instructions	Luminaire designed to be wall surface mounted.
Pictograms	