




Dimensions

Product dimensions (mm)	Ø202 x 218
Drilling hole (mm)	Ø182

Scheme

Scheme



Product

Real power (W)	28
Real luminous flux (Lm)	2194
Luminous efficiency (Lm/W)	78,4
Beam angle (°)	60
Life time (h)	50000
IP	65
IK	6
Electrical class insulation	Class 2
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	White
Energy efficiency class	A

Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,98



Light source

Light source included	Yes
Light source	Led
Nominal power (W)	25,7
Nominal luminous flux (Lm)	2523
Colour temperature (K)	3000
CRI	80

Round format fix downlight from the TROLL family Num.

DESCRIPTION

Round format fix downlight from the TROLL family Num setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as lighting of areas where waterproof features were required such as wet areas, clean rooms or outdoor porches. Designed for ceiling recessed installation. Body built in die-cast aluminium with frontal tempered glass and stainless steel fixing screws finished in white. Luminaire is IP65. Luminaire built-in an high efficiency faceted reflector made of high purity aluminium with an angle beam of 60°. Luminaire sets a 30 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 2194 Lm, with an efficiency of 78,4 Lm/W and a total consumption of 28 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.0460.8311.33
Product type	OUT
Category	Recessed
Family	Num
Subfamily	Num
Materials	Body built in die-cast aluminium with frontal tempered glass and stainless steel fixing screws.
Optical system	Luminaire built-in a high efficiency faceted reflector made of high purity aluminium.
Installation instructions	Luminaire designed for ceiling recessed installation.
Pictograms	 

Photometry

Photometry

