



Dimensions		
Product dimensions (mm)	ø120 x 148	
Packing dimensions (mm)	270 x 145 x 120	
Net weight (g)	1010	
Gross weight (Kg)	1.200	

Scheme

Scheme

Product


Real power (W)

Beam angle (°)

Life time (h)

Real luminous flux (Lm)

Luminous efficiency (Lm/W)



Spherical spotlight from the TROLL family Lumbo.

DESCRIPTION

Spherical spotlight from the TROLL family Lumbo setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimized to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for Installation on the TROLL triphasic track. Body built in Die-cast aluminium painted in ceramic white. Luminaire built-in an reflector made of high high vacuum aluminised policarbonate with an angle beam of 40° . Luminaire sets a 12 W LED source with CRI higher than 90 % and a chromatic dispersion lower than 3 SDCM. Luminaire sets a ball joint system which allows rotation 355° and tilting 90° . Fixture has a luminous flux of 1463 Lm, with an efficiency of 98,2 Lm/W and a total consumption of 15 W. The average life for the luminaire is 50000 h (established at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OF fed at 220-240V; 50/60 Hz hidden into the track adapter.

Item code	11.1426.1341.63
Product type	IN
Category	Tracklights
Family	Lumbo
Subfamily	Lumbo
Materials	Body built in Die-cast aluminium.
Optical system	Luminaire built-in an reflector made of high high vacuum aluminised policarbonate.
Installation instructions	Luminaire designed for Installation on the TROLL triphasic track.
Pictograms	









IP	20	
Electrical class insulation	Class 1	
Operating temperature	from -20°C to 35°C	
Electrical feeding	220240V, 50/60Hz	
Colour	Ceramic white	
Energy efficiency class	A +	
Control gear		
Control gear included	Yes	
Control gear	Electronic Control Gear	
Factor de potencia	0,98	
Light source		
Light source included	Yes	
Light source	Led	
Nominal power (W)	12	
Nominal luminous flux (Lm)	1568	
Average life time (h)	50000	
Colour temperature (K)	3000	
Current (mA)	350	
Colour consistency (SDCM)	3	
CRI	90	

15

1463

98,2

50000


40

Photometry

Item code 11.1426.1341.63







Accesories

11.1426.0001.04

Honeycomb antiglaring accessory for Lumbo spotlight.