Item code 11.1485.2443.33





Modular luminaire for continuous lines construction from the TROLL family Shopline.

DESCRIPTION

Modular luminaire for continuous lines construction from the TROLL family Shopline setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as lighting commercial spaces, supermarkets or warehousing areas up to 15 m ceiling height. Designed for installation on trunk that could be surface mounted or suspended. Luminaire body made from stainless steel sheet finished in white. Luminaire built-in an optical system based on a lens made of synthetic material with an angle beam of 120° . Luminaire sets a 44,8 W LED source with CRI higher than 85% and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 7762 Lm, with an efficiency of 158 Lm/W and a total consumption of 49.2 W. The average life for the luminaire is 50000 h (established at a minimum flux of 70% from the original). Luminaire built-in an DALI dimmable electronic control gear fed at $220-240V;\,50/60$ Hz.

Item code	11.1485.2443.33
Product type	IN
Category	Surface Linears
Family	Shopline
Subfamily	Shopline
Materials	Luminaire body made from stainless steel sheet.
Optical system	Luminaire built-in an optical system based on a lens made of synthetic material
Installation instructions	Luminaire designed for installation on trunk that could be surface mounted or suspended.
Pictograms	






Dimensions	
Product dimensions (mm)	79,4 x 1498 x 39,6
Packing dimensions (mm)	1549 x 390 x 210 (10 units)
Net weight (g)	4700
Gross weight (Kg)	47 (10 units)

Scheme

Scheme



Product		
Real power (W)	49,2	
Real luminous flux (Lm)	7762	
Luminous efficiency (Lm/W)	158	
Beam angle (°)	120	
Life time (h)	50000	
IP	20	
Electrical class insulation	Class 1	
Operating temperature	-20 °C to 35 °C	
Electrical feeding	220230V, 50/60Hz	
Colour	White	
Energy efficiency class	A ++	

Control gear		
Control gear included	Yes	
Control gear	DALI Dimmable Electronic Control Gear	
Factor de potencia	95	
Harmonic distortion (%)	< 15	
Light source		
Light source included	Yes	
Light source	Led	

Light source	
Light source included	Yes
Light source	Led
Nominal power (W)	44,8
Average life time (h)	50000
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80

Accesories		
11.0280.0302.00	Direct ceiling surface mounting clamp.	
11.0280.0303.00	Direct Cable suspension.	
11.0280.0304.00	Chain suspension set.	
11.0280.0305.00	Rod suspension set.	
11.0280.0307.33	End cover	
11.0281.0008.00	Feeding Connection for 8 wires trunk	
11.0281.0208.33	Terminal feeding box 8 cables	

SHOPLINE - SHOPLINE

Item code 11.1485.2443.33



11.0282.1508.33	1500 mm prewired (8 wires) trunk rail forshopline.
11.0282.3008.33	3000 mm prewired (8 wires) trunk rail for shopline.
11.0282.4508.33	4500 mm prewired (8 wires) trunk rail for shopline.
11.0283.1508.33	1500 mm prewired (8 wires) End line trunk rail for shopline.
11.1400.2000.33	Blind cover
11.1450.2000.33	Tray for three-phase track

