



#### Dimensions

|                         |                             |
|-------------------------|-----------------------------|
| Product dimensions (mm) | 79,4 x 1498 x 39,6          |
| Packing dimensions (mm) | 1549 x 390 x 210 (10 units) |
| Net weight (g)          | 4700                        |
| Gross weight (Kg)       | 47 (10 units)               |

#### Scheme

##### Scheme



#### Product

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 73,8               |
| Real luminous flux (Lm)     | 11586              |
| Luminous efficiency (Lm/W)  | 157                |
| Beam angle (°)              | R-Wallwsher        |
| Life time (h)               | 50000              |
| IP                          | 20                 |
| Electrical class insulation | Class 1            |
| Operating temperature       | -20 °C to 35 °C    |
| Electrical feeding          | 220..230V, 50/60Hz |
| Colour                      | White              |
| Energy efficiency class     | A++                |

#### Control gear

|                         |  |
|-------------------------|--|
| Control gear included   | Yes                                    |
| Control gear            | 1-10V Dimmable Electronic Control Gear |
| Factor de potencia      | 95                                     |
| Harmonic distortion (%) | < 15                                   |

#### Light source

|                           |       |
|---------------------------|-------|
| Light source included     | Yes   |
| Light source              | Led   |
| Nominal power (W)         | 67,2  |
| Average life time (h)     | 50000 |
| Colour temperature (K)    | 4000  |
| Colour consistency (SDCM) | 3     |
| CRI                       | 80    |

#### Accessories

|                 |  |
|-----------------|--|
| 11.0280.0302.00 | Direct ceiling surface mounting clamp. |
| 11.0280.0303.00 | Direct Cable suspension.               |
| 11.0280.0304.00 | Chain suspension set.                  |
| 11.0280.0305.00 | Rod suspension set.                    |
| 11.0280.0307.33 | End cover                              |
| 11.0281.0005.00 | Feeding Connection for 5 wires trunk   |
| 11.0281.0008.00 | Feeding Connection for 8 wires trunk   |

## Modular luminaire for continuous lines construction from the TROLL family Shopline.

#### DESCRIPTION

Modular luminaire for continuous lines construction from the TROLL family Shopline setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as lighting commercial spaces, supermarkets or warehousing areas up to 15 m ceiling height. Designed for installation on trunk that could be surface mounted or suspended. Luminaire body made from stainless steel sheet finished in white. Luminaire built-in an optical system based on a lens made of synthetic material with an angle beam of right asymmetric. Luminaire sets a 67,2 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 11586 Lm, with an efficiency of 157 Lm/W and a total consumption of 73,8 W. The average life for the luminaire is 50000 h (established at a minimum flux of 70 % from the original). Luminaire built-in an 1-10V dimmable electronic control gear fed at 220-240V; 50/60 Hz.

|                           |  |
|---------------------------|--|
| Item code                 | 11.1487.2462.33  |
| Product type              | IN   |
| Category                  | Surface Linears  |
| Family                    | Shopline   |
| Subfamily                 | Shopline   |
| Materials                 | Luminaire body made from stainless steel sheet.  |
| Optical system            | Luminaire built-in an optical system based on a lens made of synthetic material.         |
| Installation instructions | Luminaire designed for installation on trunk that could be surface mounted or suspended. |

#### Pictograms



|                 |  |
|-----------------|--|
| 11.0281.0205.33 | Terminal feeding box 5 cables (5 and 1cables on request)     |
| 11.0281.0208.33 | Terminal feeding box 8 cables                                |
| 11.0282.1505.33 | 1500 mm prewired (5 wires) trunk rail for shipline.          |
| 11.0282.1508.33 | 1500 mm prewired (8 wires) trunk rail for shipline.          |
| 11.0282.3005.33 | 3000 mm prewired (5 wires) trunk rail for shipline.          |
| 11.0282.3008.33 | 3000 mm prewired (8 wires) trunk rail for shipline.          |
| 11.0282.4505.33 | 4500 mm prewired (5 wires) trunk rail for shipline.          |
| 11.0282.4508.33 | 4500 mm prewired (8 wires) trunk rail for shipline.          |
| 11.0283.1505.33 | 1500 mm prewired (5 wires) end line trunk rail for shipline. |
| 11.0283.1508.33 | 1500 mm prewired (8 wires) End line trunk rail for shipline. |
| 11.1400.2000.33 | Blind cover  |
| 11.1450.2000.33 | Tray for three-phase track                                   |