


Dimensions		
Product dimensions (mm)	125 x 125 x 134	
Packing dimensions (mm)	135 x 135 x 144	
Net weight (g)	1423	
Drilling hole (mm)	110 x 110	

Scheme

Scheme



Single head square downlight with small format from the TROLL family Mini Zas Cardan.

DESCRIPTION

Single head square downlight with small format from the TROLL family Mini Zas Cardan setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as general indoor lighting for offices, hospitals commercial areas or residential & contract spaces. Designed for ceiling recessed installation. Luminaire body made from Lacquered stainless steel sheet with headlights and heat-sinks built in die cast aluminium finished in grey. Luminaire is IP20. Luminaire built-in an head setting faceted reflector made in high purity aluminium with an angle beam of 20°. Luminaire sets a 25 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Luminaire sets a ball joint system which allows 25° in both cardanic axels. Fixture has a luminous flux of 2108 Lm, with an efficiency of 72,7 Lm/W and a total consumption of 29 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OF fed at 220-240V; 50/60 Hz.

Lm, with an efficiency of 72,7 Lm/W and a total consumption of 29 W. The average life the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OF fed at 220-240V; 50/60 Hz.			
Item code	11.1518.2831.21		
Product type	IN		
Category	Recessed Downlights		
Family	Zas		
Subfamily	Mn Zas Cardan		
Materials	Luminaire body made from Lacquered stainless steel sheet with headlights and		

Pictograms

Optical system

Installation instructions







heat-sinks built in die cast aluminium. Luminaire built-in a head setting faceted

reflector made in high purity aluminium. Luminaire designed for ceiling recessed

Product		
rroduct		
Real power (W)	29	
Real luminous flux (Lm)	2108	
Luminous efficiency (Lm/W)	72,7	
Beam angle (°)	25	
Life time (h)	50000	
IP	20	
Electrical class insulation	Class 2	
Operating temperature	from -20°C to 35°C	
Electrical feeding	220240V, 50/60Hz	
Colour	Grey	
Energy efficiency class	A	

Control gear		
Control gear included	Yes	
Control gear	Electronic Control Gear	
Factor de potencia	0,99	
Light source		
Light source included	Yes	
Light source	Led	
Nominal power (W)	25	
Nominal luminous flux (Lm)	3400	
Average life time (h)	50000	
Colour temperature (K)	3000	
Colour consistency (SDCM)	3	
CRI	80	

Photometry



Photometry

