




Dimensions

Product dimensions (mm)	ø105 x 87
Net weight (g)	287
Drilling hole (mm)	Ø95

Scheme

Scheme



Product

Real power (W)	16,7
Real luminous flux (Lm)	1036
Luminous efficiency (Lm/W)	62
Beam angle (°)	40
Life time (h)	50000
IP	44/20
Electrical class insulation	Class 2
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	White
Energy efficiency class	A

Control gear


Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,94

Light source

Light source included	Yes
Light source	Led
Nominal power (W)	15
Nominal luminous flux (Lm)	1300
Colour temperature (K)	4000
CRI	80

Photometry

Photometry



Accessories

11.1547.5001.33	15W - Fixed.
-----------------	--------------

Picture



11.1547.5002.33	15W - Fixed / orientable.
-----------------	---------------------------

Picture



11.1547.5004.33	15W - Fixed / orientable.
-----------------	---------------------------

Picture



11.1547.5006.33	15W - Fixed / orientable square.
-----------------	----------------------------------

Picture



11.1547.5007.33	15W - Fixed / orientable square.
-----------------	----------------------------------

Picture

