




Dimensions

| | |
|-------------------------|-----------|
| Product dimensions (mm) | ø105 x 87 |
| Net weight (g) | 287 |
| Drilling hole (mm) | Ø95 |

Scheme

Scheme



Small format adjustable downlight from the TROLL family Pinhole.

DESCRIPTION

Small format adjustable downlight from the TROLL family Pinhole setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as light effects creation in hotels, offices or commercial areas where small format fixtures are required. Designed for ceiling recessed installation. Luminaire body made of synthetic material with die-cast aluminium heat-sink finished in white. Optical group is IP44 on the visible frontal area. Luminaire built-in an high purity aluminium reflector with frontal diffuser with an angle beam of 24°. Luminaire sets a 15 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SMCD. Luminaire sets a ball joint system which allows tilting 20°. Fixture has a luminous flux of 1054 Lm, with an efficiency of 63,1 Lm/W and a total consumption of 16,7 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

| | |
|---------------------------|--|
| Item code | 11.1547.5412.33 |
| Product type | IN |
| Category | Recessed Downlights |
| Family | Pinhole |
| Subfamily | Pinhole |
| Materials | Luminaire body made of synthetic material with die-cast aluminium heat-sink. |
| Optical system | Luminaire built-in a high purity aluminium reflector with frontal diffuser. |
| Installation instructions | Luminaire designed for ceiling recessed installation. |

Pictograms



Product

| | |
|-----------------------------|--------------------|
| Real power (W) | 16,7 |
| Real luminous flux (Lm) | 1054 |
| Luminous efficiency (Lm/W) | 63,1 |
| Beam angle (°) | 24 |
| Life time (h) | 50000 |
| IP | 44/20 |
| Electrical class insulation | Class 2 |
| Operating temperature | from -20°C to 35°C |
| Electrical feeding | 220..240V, 50/60Hz |
| Colour | White |
| Energy efficiency class | A |

Control gear


| | |
|-----------------------|-------------------------|
| Control gear included | Yes |
| Control gear | Electronic Control Gear |
| Factor de potencia | 0,94 |

Light source

| | |
|----------------------------|------|
| Light source included | Yes |
| Light source | Led |
| Nominal power (W) | 15 |
| Nominal luminous flux (Lm) | 1300 |
| Colour temperature (K) | 4000 |
| CRI | 80 |

Photometry

Photometry



Accessories

11.1547.5002.33**15W - Fixed / orientable.**

Picture

11.1547.5003.33

15W - Orientable.

Picture

11.1547.5004.33

15W - Fixed / orientable.

Picture

11.1547.5005.33

Fixed / orientable.

Picture

11.1547.5006.33

15W - Fixed / orientable square.

Picture



11.1547.5007.33

15W - Fixed / orientable square.

Picture

