CONTRACT - CONTRACT A

Adjustable round downlight from the TROLL family Contract.

DESCRIPTION

Adjustable round downlight from the TROLL family Contract setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for ceiling recessed installation. Luminaire body built in die-cast aluminium finished in white. Optical group is IP44 on the visible frontal area. Luminaire built-in an primary reflector made of high purity aluminium plus an antiglare secondary reflector. with an angle beam of 30°. Luminaire sets a 7 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Luminaire sets a ball joint system which allows rotation 355° and tilting 30°. Fixture has a luminous flux of 650 Lm, with an efficiency of 72,2 Lm/W and a total consumption of 9 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear Dimmable 1-10V fed at

Item code	11.1601.1034.33	
Product type	IN	
Category	Recessed Downlights	
Family	Contract	
Subfamily	Contract A	
Materials	Luminaire body built in die-cast aluminium.	
Optical system	Luminaire built-in a primary reflector made of high purity aluminium plus an antiglare secondary reflector	
Installation instructions	Luminaire designed for ceiling recessed installation.	
Pictograms		

Item code 11.1601.1034.33

Product dimensions (mm)	Ø87 x 91
Net weight (g)	450
Gross weight (Kg)	0,53
Drilling hole (mm)	Ø 75

Scheme

Scheme



Product		
Real power (W)	9	
Real luminous flux (Lm)	650	
U.G.R. (%)	< 19	
Luminous efficiency (Lm/W)	72,2	
Beam angle (°)	30	
Life time (h)	50000	
IP	44/20	
Electrical class insulation	Class 2	
Operating temperature	from -20°C to 35°C	
Electrical feeding	220240V, 50/60Hz	
Colour	White	
Energy efficiency class	Α	

Control gear		
Control gear included	Yes	
Control gear	1-10V Dimmable Electronic Control Gear	
Factor de potencia	0,99	

Light source	
Light source included	Yes
Light source	Led
Nominal power (W)	7
Nominal luminous flux (Lm)	800
Colour temperature (K)	3000
Colour consistency (SDCM)	3
CRI	80

Accesories	
11.1603.0012.04	Honeycomb mesh for 7W.
11.1603.0111.04	Reflector for 7W.
11.1603.0111.33	Reflector for 7W.

