




**Dimensions**

Product dimensions (mm)	Ø164 x 148
Net weight (g)	1020
Gross weight (Kg)	1,1
Drilling hole (mm)	Ø 150

**Scheme**




Scheme



**Round format fix downlight from the TROLL family Contract.**

**DESCRIPTION**

Round format fix downlight from the TROLL family Contract setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for ceiling recessed installation. Luminaire body built in die-cast aluminium finished in white. Optical group is IP44 on the visible frontal area. Luminaire built-in a primary reflector made of high purity aluminium plus an antiglare secondary reflector, with an angle beam of 15°. Luminaire sets a 25 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Luminaire UGR<19. Fixture has a luminous flux of 2300 Lm, with an efficiency of 82,14 Lm/W and a total consumption of 28 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.1602.4831.33
Product type	IN
Category	Recessed Downlights
Family	Contract
Subfamily	Contract F
Materials	Luminaire body built in die-cast aluminium.
Optical system	Luminaire built-in a primary reflector made of high purity aluminium plus an antiglare secondary reflector..
Installation instructions	Luminaire designed for ceiling recessed installation.
Pictograms	  

**Product**

Real power (W)	28
Real luminous flux (Lm)	2300
U.G.R. (%)	< 19
Luminous efficiency (Lm/W)	82,14
Beam angle (°)	15
Life time (h)	50000
IP	44/20
Electrical class insulation	Class 2
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	White
Energy efficiency class	A

**Control gear**


Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,99

**Light source**

Light source included	Yes
Light source	Led
Nominal power (W)	25
Nominal luminous flux (Lm)	3100
Colour temperature (K)	3000
Colour consistency (SDCM)	3
CRI	80

**Photometry**

**Photometry**



**Accessories**

11.1603.0041.04	Reflector for 24-32W.
11.1603.0041.33	Reflector for 24-32W.
11.1603.0042.04	Honeycomb mesh for 24-32W.