



**Dimensions**

|                         |            |
|-------------------------|------------|
| Product dimensions (mm) | Ø164 x 163 |
| Net weight (g)          | 1080       |
| Gross weight (Kg)       | 1,16       |
| Drilling hole (mm)      | Ø 150      |

**Scheme**




Scheme



**Round format fix downlight from the TROLL family Contract.**

**DESCRIPTION**

Round format fix downlight from the TROLL family Contract setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as general & accent lighting for commercial areas shop-windows and different indoor spaces. Designed for ceiling recessed installation. Luminaire body built in die-cast aluminium finished in white. Optical group is IP44 on the visible frontal area. Luminaire built-in a primary reflector made of high purity aluminium plus an antiglare secondary reflector. with an angle beam of 60°. Luminaire sets a 32 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Luminaire UGR<19. Fixture has a luminous flux of 3090 Lm, with an efficiency of 85,8 Lm/W and a total consumption of 36 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear Dimmable 1-10V fed at 220-240V; 50/60 Hz.

|                           |   |
|---------------------------|---|
| Item code                 | 11.1602.5046.33   |
| Product type              | IN  |
| Category                  | Recessed Downlights   |
| Family                    | Contract  |
| Subfamily                 | Contract F  |
| Materials                 | Luminaire body built in die-cast aluminium.   |
| Optical system            | Luminaire built-in a primary reflector made of high purity aluminium plus an antiglare secondary reflector..  |
| Installation instructions | Luminaire designed for ceiling recessed installation.   |
| Pictograms                |    |

**Product**

|                             |                      |
|-----------------------------|----------------------|
| Real power (W)              | 36                   |
| Real luminous flux (Lm)     | 3090                 |
| U.G.R. (%)                  | < 19                 |
| Luminous efficiency (Lm/W)  | 85,8                 |
| Beam angle (°)              | 60                   |
| Life time (h)               | 50000                |
| IP                          | 44/20                |
| Electrical class insulation | Class 2              |
| Operating temperature       | from -20° C to 35° C |
| Electrical feeding          | 220..240V, 50/60Hz   |
| Colour                      | White                |
| Energy efficiency class     | A+                   |

**Control gear**

|                       |  |
|-----------------------|--|
| Control gear included | Yes                                    |
| Control gear          | 1-10V Dimmable Electronic Control Gear |
| Factor de potencia    | 0,99                                   |

**Light source**

|                            |      |
|----------------------------|------|
| Light source included      | Yes  |
| Light source               | Led  |
| Nominal power (W)          | 32   |
| Nominal luminous flux (Lm) | 4300 |
| Colour temperature (K)     | 4000 |
| Colour consistency (SDCM)  | 3    |
| CRI                        | 80   |

**Photometry**

Photometry

