



#### Dimensions

|                         |                 |
|-------------------------|-----------------|
| Product dimensions (mm) | 64 x 1150 x 59  |
| Packing dimensions (mm) | 75 x 1195 x 115 |
| Net weight (g)          | 2027            |
| Gross weight (Kg)       | 2,5             |

#### Scheme

##### Scheme



#### Product

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 41                 |
| Real luminous flux (Lm)     | 5728               |
| Luminous efficiency (Lm/W)  | 139,8              |
| Beam angle (°)              | R-Wallwasher       |
| Life time (h)               | 50000              |
| IP                          | 44                 |
| Electrical class insulation | Class 1            |
| Operating temperature       | from -25°C to 45°C |
| Electrical feeding          | 220..240V, 50/60Hz |
| Colour                      | Ceramic white      |
| Energy efficiency class     | A+                 |

#### Control gear


|                       |                         |
|-----------------------|-------------------------|
| Control gear included | Yes                     |
| Control gear          | Electronic Control Gear |
| Factor de potencia    | 0,95                    |

#### Light source

|                            |       |
|----------------------------|-------|
| Light source included      | Yes   |
| Light source               | Led   |
| Nominal power (W)          | 38,4  |
| Nominal luminous flux (Lm) | 6456  |
| Average life time (h)      | 50000 |
| Colour temperature (K)     | 4000  |
| Current (mA)               | 300   |
| Colour consistency (SDCM)  | 3     |
| CRI                        | 80    |

#### Photometry



##### Photometry



## Track mounted luminaire Box from the TROLL T-Tris system.

#### DESCRIPTION

Track mounted luminaire Box from the TROLL T-Tris system setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as general lighting for commercial areas shop-windows and different indoor spaces. Designed for installation on the TROLL triphasic track. Luminaire body made from stainless steel sheet finished in ceramic white. Luminaire is IP44. Luminaire built-in an independent lens system for each led with a wallwasher beam (right). Luminaire sets a 38,4 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SMDC. Fixture has a luminous flux of 5728 Lm, with an efficiency of 139,8 Lm/W and a total consumption of 41 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear on/off fed at 220-240V; 50/60 Hz.

|                           |   |
|---------------------------|---|
| Item code                 | 11.1670.4461.63   |
| Product type              | IN  |
| Category                  | Tracklights   |
| Family                    | T-Tris System   |
| Subfamily                 | T-Tris Box  |
| Materials                 | Luminaire body made from stainless steel sheet.   |
| Optical system            | Luminaire built-in a independent lens system for each led.  |
| Installation instructions | Luminaire designed for Installation on the TROLL triphasic track.   |
| Pictograms                |   |