T-TRIS SYSTEM - T-TRIS BOX

Item code 11.1670.5441.63

and the first first first second and the second

Track mounted luminaire Box from the TROLL T-Tris system.

DESCRIPTION


Track mounted luminaire Box from the TROLL T-Tris system setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as general lighting for commercial areas shop-windows and different indoor spaces. Designed for Installation on the TROLL triphasic track. Luminaire body made from stainless steel sheet finished in ceramic white. Luminaire is IP44. Luminaire built-in an independent lens system for each led with an angle beam of 110°. Luminaire sets a 57,6 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SMDC. Fixture has a luminous flux of 8538 Lm, with an efficiency of 137,7 Lm/W and a total consumption of 62 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear on/off fed at 220-240V; 50/60 Hz.

Item code	11.1670.5441.63
Product type	IN
Category	Tracklights
Family	T-Tris System
Subfamily	T-Tris Box
Materials	Luminaire body made from stainless steel sheet.
Optical system	Luminaire builts-in a independent lens system for each led.
Installation instructions	Luminaire designed for Installation on the TROLL triphasic track.
Pictograms	((

Product dimensions (mm)	127 x 864 x 59	
Packing dimensions (mm)	138 x 910 x 115	
Net weight (g)	2917	
Gross weight (Kg)	3,3	

Scheme

Scheme



Product		
Real power (W)	62	
Real luminous flux (Lm)	8538	
Luminous efficiency (Lm/W)	137,7	
Beam angle (°)	110	
Life time (h)	50000	
IP	44	
Electrical class insulation	Class 1	
Operating temperature	from -25°C to 45°C	
Electrical feeding	220240V, 50/60Hz	
Colour	Ceramic white	
Energy efficiency class	A+	

Control gear			
Control gear included	Yes		
Control gear	Electronic Control Gear		
Factor de potencia	0,95		

Light source		
Light source included	Yes	
Light source	Led	
Nominal power (W)	38,4	
Nominal luminous flux (Lm)	6456	
Average life time (h)	50000	
Colour temperature (K)	4000	
Colour consistency (SDCM)	3	
CRI	80	

tr●ll®

LUXIONA