




#### Dimensions

Product dimensions (mm)	36 x 845 x 63
Packing dimensions (mm)	45 x 915 x 125

#### Scheme

Scheme



#### Product

Real power (W)	22,5
Real luminous flux (Lm)	1611
Luminous efficiency (Lm/W)	71,6
Beam angle (°)	75
Life time (h)	50000
IP	40
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Ceramic white
Energy efficiency class	A

#### Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,94




#### Light source

Light source included	Yes
Light source	Led
Nominal power (W)	20
Nominal luminous flux (Lm)	3100
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80

## 845 mm length minimalist LED linear luminaire from the TROLL family T-Tris.

#### DESCRIPTION

845 mm length minimalist LED linear luminaire from the TROLL family T-Tris setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as general indoor lighting for offices, hospitals commercial areas or residential & contract spaces. Designed for installation on the TROLL triphasic track. Luminaire body built in extruded aluminium finished in white. Luminaire is IP40. Luminaire built-in a Polycarbonate opal diffuser with an angle beam of 85°. Luminaire sets a 20 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 1611 Lm, with an efficiency of 71,6 Lm/W and a total consumption of 22,5 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.1671.3104.63
Product type	IN
Category	Tracklights
Family	T-Tris System
Subfamily	T-Tris Line
Materials	Luminaire body built in extruded aluminium.
Optical system	Luminaire built-in a Polycarbonate opal diffuser.
Installation instructions	Luminaire designed for installation on the TROLL triphasic track.
Pictograms	  

Photometry

Photometry

