




---

**Dimensions**


---

|                         |                 |
|-------------------------|-----------------|
| Product dimensions (mm) | 36 x 1125 x 63  |
| Packing dimensions (mm) | 45 x 1195 x 125 |

---



---

**Scheme**


---

Scheme




---

**Product**


---

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 22                 |
| Real luminous flux (Lm)     | 1677               |
| Luminous efficiency (Lm/W)  | 76,2               |
| Beam angle (°)              | 75                 |
| Life time (h)               | 50000              |
| IP                          | 40                 |
| Electrical class insulation | Class 1            |
| Operating temperature       | from -20°C to 35°C |
| Electrical feeding          | 220..240V, 50/60Hz |
| Colour                      | Ceramic white      |
| Energy efficiency class     | A                  |

---



---

**Control gear**


---

|                       |                                       |
|-----------------------|---------------------------------------|
| Control gear included | Yes                                   |
| Control gear          | DALI Dimmable Electronic Control Gear |
| Factor de potencia    | 0,94                                  |

---



---

**Light source**


---

|                            |      |
|----------------------------|------|
| Light source included      | Yes  |
| Light source               | Led  |
| Nominal power (W)          | 19,5 |
| Nominal luminous flux (Lm) | 2700 |
| Colour temperature (K)     | 3000 |
| Colour consistency (SDCM)  | 3    |
| CRI                        | 80   |

---






---

## 1125 mm length minimalist LED linear luminaire from the TROLL family T-Tris.

---

**DESCRIPTION**

1125 mm length minimalist LED linear luminaire from the TROLL family T-Tris setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as general indoor lighting for offices, hospitals commercial areas or residential & contract spaces. Designed for installation on the TROLL triphasic track. Luminaire body built in extruded aluminium finished in white. Luminaire is IP40. Luminaire built-in a Polycarbonate opal diffuser with an angle beam of 85°. Luminaire sets a 19,5 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 1677 Lm, with an efficiency of 76,2 Lm/W and a total consumption of 22 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear DALI dimmable fed at 220-240V; 50/60 Hz.

|                           |   |
|---------------------------|---|
| Item code                 | 11.1671.3205.63   |
| Product type              | IN  |
| Category                  | Tracklights   |
| Family                    | T-Tris System   |
| Subfamily                 | T-Tris Line   |
| Materials                 | Luminaire body built in extruded aluminium.   |
| Optical system            | Luminaire built-in a Polycarbonate opal diffuser.   |
| Installation instructions | Luminaire designed for installation on the TROLL triphasic track.   |
| Pictograms                |    |

Photometry

Photometry

