




#### Dimensions

Product dimensions (mm)	159 x 365 x 107
Net weight (g)	3700
Gross weight (Kg)	3,85

#### Scheme




Scheme



## LED Outdoor projector from the TROLL family Ledmotiv.

#### DESCRIPTION

LED Outdoor projector from the TROLL family Ledmotiv setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as lighting of gardens, façades or fountains and all outdoor applications requiring light projection. Designed for floor wall or ceiling surface mounted. Luminaire body built in die-cast aluminium finished in grey. Luminaire is IP65 and IK08. Luminaire built-in an high purity aluminium reflector with tempered protection glass with an angle beam of 36°. Luminaire sets a 51 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SMCD. Luminaire sets a ball joint system which allows tilting 90°. Fixture has a luminous flux of 5740 Lm, with an efficiency of 102 Lm/W and a total consumption of 56,5 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.1673.2431.21
Product type	OUT
Category	Projectors
Family	Ledmotiv
Subfamily	Ledmotiv
Materials	Luminaire body built in die-cast aluminium.
Optical system	Luminaire built-in a high purity aluminium reflector with tempered protection glass.
Installation instructions	Luminaire designed for floor wall or ceiling surface mounted.
Pictograms	  

#### Product

Real power (W)	56,5
Real luminous flux (Lm)	5740
Luminous efficiency (Lm/W)	102
Beam angle (°)	36
Life time (h)	50000
IP	65
IK	08
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Grey
Energy efficiency class	A+

#### Control gear

Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,96
Flicker index (%)	< 5

#### Light source

Light source included	Yes
Light source	Led
Nominal power (W)	51
Nominal luminous flux (Lm)	6100
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	80

#### Photometry

Photometry

