


---

**Dimensions**


---

Product dimensions (mm)	75 x 45 x 50
Drilling hole (mm)	35 x 65

---




---

**Scheme**


---

Scheme







---

### Small format fix downlight from the TROLL family Microlinear.

---

**DESCRIPTION**

Small format fix downlight from the TROLL family Microlinear setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 2700° K (warm white) optimised to be used as general lighting of commercial or domestic areas, as well as contract spaces where aesthetic and design were a relevant requirement. Designed for ceiling recessed installation. Body built in die-cast aluminium with plastic buffer in black and finished in black. Luminaire built-in an faceted microreflectors made of plastic material aluminised at vacuum with an angle beam of 45°. Luminaire sets a 2 W LED source with CRI higher than 90 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 324 Lm, with an efficiency of 65 Lm/W and a total consumption of 5 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.1701.2241.04
Product type	IN
Category	Recessed Downlights
Family	Microdownlights
Subfamily	Microlinear
Materials	Body built in die-cast aluminium with plastic buffer in black and.
Optical system	Luminaire built-in a faceted microreflectors made of plastic material aluminised at vacuum.
Installation instructions	Luminaire designed for ceiling recessed installation.
Pictograms	  

---

**Product**


---

Real power (W)	5
Real luminous flux (Lm)	324
Luminous efficiency (Lm/W)	65
Beam angle (°)	45
Life time (h)	50000
IP	20
Electrical class insulation	Class 2
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Black
Energy efficiency class	A

---



---

**Control gear**


---

Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,95

---



---

**Light source**


---

Light source included	Yes
Light source	Led
Nominal power (W)	4
Nominal luminous flux (Lm)	220
Average life time (h)	50000
Colour temperature (K)	2700
Colour consistency (SDCM)	3
CRI	90

---



---

**Photometry**


---

Photometry

