




---

**Dimensions**


---

|                         |            |
|-------------------------|------------|
| Product dimensions (mm) | ø218 x 138 |
| Net weight (g)          | 743        |
| Drilling hole (mm)      | Ø200       |

---



---

**Scheme**



---



---

**Scheme**


---




---

**Product**


---

|                             |                    |
|-----------------------------|--------------------|
| Real power (W)              | 36                 |
| Real luminous flux (Lm)     | 3669               |
| U.G.R. (%)                  | < 19               |
| Luminous efficiency (Lm/W)  | 102                |
| Beam angle (°)              | 80                 |
| Life time (h)               | 50000              |
| IP                          | 20                 |
| Electrical class insulation | Class 2            |
| Operating temperature       | from -20°C to 35°C |
| Electrical feeding          | 220..240V, 50/60Hz |
| Colour                      | White              |
| Energy efficiency class     | A+                 |

---



---

**Control gear**


---

|                       |                                     |
|-----------------------|-------------------------------------|
| Control gear included | Yes                                 |
| Control gear          | Electronic Control Gear & Emergency |
| Factor de potencia    | 0,98                                |

---



---

**Light source**


---

|                            |       |
|----------------------------|-------|
| Light source included      | Yes   |
| Light source               | Led   |
| Nominal power (W)          | 31,7  |
| Nominal luminous flux (Lm) | 5000  |
| Average life time (h)      | 50000 |
| Colour temperature (K)     | 3000  |
| Current (mA)               | 900   |
| Colour consistency (SDCM)  | 3     |
| CRI                        | 80    |

---



---

**Photometry**


---



---


## Round format fix downlight from the TROLL family Optics Comfort.

---

**DESCRIPTION**

Round format fix downlight from the TROLL family Optics Comfort setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as general indoor lighting for offices, hospitals commercial areas or residential & contract spaces. Designed for ceiling recessed installation. Luminaire body built in synthetic material and aluminium heat-sink with finishes in white. Luminaire is IP20. Luminaire built-in an high efficiency reflector made of high vacuum aluminised polycarbonate with an angle beam of 80°. Luminaire sets a 31,5 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SMCD. Luminaire UGR<19. Fixture has a luminous flux of 3669 Lm, with an efficiency of 102 Lm/W and a total consumption of 36 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an electronic control gear with emergency kit fed at 220-240V; 50/60 Hz.

|                           |   |
|---------------------------|---|
| Item code                 | 11.1703.3304.33   |
| Product type              | IN  |
| Category                  | Recessed Downlights   |
| Family                    | Optics  |
| Subfamily                 | Optics Comfort  |
| Materials                 | Luminaire body built in synthetic material with aluminium heat-sink.                          |
| Optical system            | Luminaire built-in a high efficiency reflector made of high vacuum aluminised polycarbonate . |
| Installation instructions | Luminaire designed for ceiling recessed installation.   |
| Pictograms                |   |



Photometry

