




Dimensions

Product dimensions (mm)	225 x 43 x 30,2
-------------------------	-----------------

Scheme

Scheme



Product

Real power (W)	60
Life time (h)	50000
IP	20
Electrical class insulation	Class 2
Operating temperature	from -25° to 50°
Electrical feeding	220..240V, 50/60Hz
Colour	White

Control gear

Factor de potencia	0,98
Harmonic distortion (%)	< 6
Flicker index (%)	5

60W DALI dimmable power supply driver from the Troll family DALI DriverP.

DESCRIPTION

60W DALI dimmable power supply driver from the Troll family DALI DriverP. Driver provides constant output voltage at 24V. Small format Driver with high efficiency and low losses. It is protected against overload and over-temperature. Disconnection by short-circuit with automatic switching. Driver Complies with Class C from minimum to maximum load range according to EN 61000-3-2. Driver suitable for scape lighting systems according to EN 50172. In addition driver accomplish with norms: EN55015; EN 60598-2-22; EN 6100-3-2; EN 61000-3-3; EN 61347-1; EN 61347-2-13; EN 61547; EN 62384 & EN62383-101 (according to DALI standard V2); EN62386-102 & EN 62386-207. Fed at 220-240V; 50/60Hz.

Item code	11.1801.7031.00
-----------	-----------------

Product type	CONTROL
--------------	---------

Category	Power supply
----------	--------------

Family	DALI
--------	------

Subfamily	DriverP
-----------	---------

Installation instructions	Driver for independet use.
---------------------------	----------------------------

Pictograms

