



100W DALI dimmable power supply driver from the Troll family DALI DriverP.

DESCRIPTION

100W DALI dimmable power supply driver from the Troll family DALI DriverP. Driver provides constant output voltage at 24V. Small format Driver with high efficiency and low loses. It is protected against overload and over-temperature. Disconnection by short-circuit with automatic switching. Driver Complish with Class C from minimum to maximum load range according to EN 61000-3-2. Driver suitable for scape lighting systems according to EN 50172. In addition driver accomplish with norms: EN55015; EN 60598-2-22; EN 6100-3-2; EN 61000-3-3; EN 61347-1; EN 61347-2-13; EN 61547; EN 62384 & EN62383-101 (according to DALI standard V2); EN62386-102 & EN 62386-207. Fed at 220-240V; 50/60Hz.

Item code	11.1801.7032.00
Product type	CONTROL
Category	Power supply
Family	DALI
Subfamily	DriverP
Installation instructions	Driver for independet use.

Pictograms



cheme
cheme

Product		
Real power (W)	100	
Life time (h)	50000	
IP	20	
Electrical class insulation	Class 2	
Operating temperature	from -25 $^{\circ}$ to 50 $^{\circ}$	
Electrical feeding	220240V, 50/60Hz	
Colour	White	

Control gear		
Factor de potencia	0,99	
Harmonic distortion (%)	< 6	
Flicker index (%)	5	