## Item code 11.1833.1311.04





## Mono-directional wallwashwer tracklight from the TROLL family T-Tris.

## DESCRIPTION

Mono-directional wallwashwer tracklight from the TROLL family T-Tris setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of  $3000^\circ$  K (warm white) optimised to be used in retail food spaces as well as in museums or art galleries. Designed for Installation on the TROLL triphasic track. Body built in steel sheet painted with high quality coatings finished in black. Luminaire built-in an asymmetric technical reflector with an asymmetrical distribution at  $25^\circ$ . Luminaire sets a 17 W LED source with CRI higher than 80% and a chromatic dispersion lower than 3 SDCM. Luminaire sets a ball joint system which allows rotation  $355^\circ$ . Fixture has a luminous flux of 1930 Lm, with an efficiency of 101,6 Lm/W and a total consumption of 19 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70% from the original). Luminaire built-in an auxiliary gear ON/OF fed at 220-240V; 50/60 Hz.

Item code	11.1833.1311.04
Product type	IN
Category	Tracklights
Family	T-Tris System
Subfamily	T-Tris L
Materials	Body built in steel sheet painted with high quality coatings.
Optical system	Luminaire built-in an asymmetric technical reflector with an asymmetrical distribution at 25°.
Installation instructions	Mono-directional wallwashwer tracklight from the TROLL family T-Tris.
Pictograms	

Dimensions		
Product dimensions (mm)	88 x 275 x 171	
Net weight (g)	1215	

Product		
Real power (W)	19	
Real luminous flux (Lm)	1930	
Luminous efficiency (Lm/W)	101,6	
Life time (h)	50000	
IP	20	
Electrical class insulation	Class 1	
Operating temperature	from -20°C to 35°C	
Electrical feeding	220240V, 50/60Hz	
Colour	Black	
Energy efficiency class	<b>A</b> +	

Control gear		
Control gear included	Yes	
Control gear	Electronic Control Gear	

T to be accessed		
Light source		
Light source included	Yes	
Light source	Led	
Nominal power (W)	17	
Nominal luminous flux (Lm)	2500	
Colour temperature (K)	3000	
Colour consistency (SDCM)	3	
CRI	90	

## Photometry

Photometry





