



#### Dimensions

Product dimensions (mm) 88 x 275 x 171

#### Product

Real power (W) 19  
 Real luminous flux (Lm) 2100  
 Luminous efficiency (Lm/W) 110,5  
 Life time (h) 50000  
 IP 20  
 Electrical class insulation Class 1  
 Operating temperature from -20°C to 35°C  
 Electrical feeding 220..240V, 50/60Hz  
 Colour Ceramic white  
 Energy efficiency class A+

#### Control gear


Control gear included Yes  
 Control gear Electronic Control Gear

#### Light source

Light source included Yes  
 Light source Led  
 Nominal power (W) 17  
 Nominal luminous flux (Lm) 2730  
 Colour temperature (K) 4000  
 Colour consistency (SDCM) 3  
 CRI 90

#### Photometry

##### Photometry



## Mono-directional wallwasher tracklight from the TROLL family T-Tris.

#### DESCRIPTION

Mono-directional wallwasher tracklight from the TROLL family T-Tris setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used in retail food spaces as well as in museums or art galleries. Designed for installation on the TROLL triphasic track. Body built in steel sheet painted with high quality coatings finished in white. Luminaire built-in an asymmetric technical reflector with an asymmetrical distribution at 25°. Luminaire sets a 17 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SDCM. Luminaire sets a ball joint system which allows rotation 355°. Fixture has a luminous flux of 2100 Lm, with an efficiency of 110,5 Lm/W and a total consumption of 19 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.1833.1411.63
Product type	IN
Category	Tracklights
Family	T-Tris System
Subfamily	T-Tris L
Materials	Body built in steel sheet painted with high quality coatings.
Optical system	Luminaire built-in an asymmetric technical reflector with an asymmetrical distribution at 25°.
Installation instructions	Luminaire designed for installation on the TROLL triphasic track.

#### Pictograms

