









### Decorative and minimalist luminaire with neutral aesthetic from the TROLL family Tubular LED.

#### DESCRIPTION

Decorative and minimalist luminaire with neutral aesthetic from the TROLL family Tubular LED setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 4000° K (neutral white) optimised to be used as general lighting of commercial or domestic areas, as well as contract spaces where aesthetic and design were a relevant requirement. Designed for Ceiling suspended installation. Luminaire body built in extruded aluminium finished in anthracite with orange interior Luminaire built-in an high purity aluminium reflector with tempered protection glass with an angle beam of 24°. Luminaire sets a 17 W LED source with CRI higher than 85 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 2120 Lm, with an efficiency of 106 Lm/W and a total consumption of 20 W. The average life for the luminaire is 50000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.2645.1421.22
Product type	IN
Category	Surface Downlights
Family	Tubular-S
Subfamily	Tubular M
Materials	Luminaire body built in extruded aluminium.
Optical system	Luminaire built-in a high purity aluminium reflector with tempered protection glass.
Installation instructions	Luminaire designed for Ceiling suspended installation.
Pictograms	     


<b>Dimensions</b>	
Product dimensions (mm)	ø108 x 345
Net weight (g)	1800
<b>Product</b>	
Real power (W)	20
Real luminous flux (Lm)	2120
Luminous efficiency (Lm/W)	106
Beam angle (°)	24
Life time (h)	50000
IP	20
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Anthracite
Energy efficiency class	A+

<b>Control gear</b>	
Control gear included	Yes
Control gear	Electronic Control Gear
Factor de potencia	0,99

<b>Light source</b>	
Light source included	Yes
Light source	Led
Nominal power (W)	17
Nominal luminous flux (Lm)	2300
Colour temperature (K)	4000
Colour consistency (SDCM)	3
CRI	90

#### Photometry

#### Photometry



<b>Accessories</b>	
11.1645.0001.22	On-Off base area
11.1645.0002.22	On-Off half-surface area