




---

**Dimensions**


---

Product dimensions (mm)	80 x 255 x 76
Drilling hole (mm)	70 x 240

---




---

**Scheme**


---

Scheme




---

**Product**


---

Real power (W)	6,65
Real luminous flux (Lm)	56
Beam angle (°)	120
Life time (h)	35000
IP	65
IK	9
Electrical class insulation	Class 1
Operating temperature	from -20°C to 35°C
Electrical feeding	220..240V, 50/60Hz
Colour	Stainless steel
Energy efficiency class	A

---



---

**Control gear**


---

Control gear included	Yes
Control gear	Electronic Control Gear

---



---

**Light source**


---

Light source included	Yes
Light source	Led
Nominal power (W)	6,5
Nominal luminous flux (Lm)	66
Colour temperature (K)	3000
CRI	80

---



---

**Lighting and beaconing luminaire from the TROLL family E-wall.**


---

**DESCRIPTION**

Lighting and beaconing luminaire from the TROLL family E-wall setting an advanced and innovative thermal balance system through passive dissipation with stable colour temperature of 3000° K (warm white) optimised to be used as flush floor lighting and beaconing of passing areas in indoor and outdoor installations. Designed for wall recessed installed. Body built in die-cast aluminium with the frontal made of tempered glass and stainless steel finished in Polish steel. Luminaire is IP65 and IK10. Luminaire built-in an opal diffuser that could be complemented with antiglare louver with an angle beam of 120°. Luminaire sets a 7 W LED source with CRI higher than 80 % and a chromatic dispersion lower than 3 SMCD. Fixture has a luminous flux of 56 Lm, with an efficiency of Lm/W and a total consumption of 6,65 W. The average life for the luminaire is 35000 h (stabilised at a minimum flux of 70 % from the original). Luminaire built-in an auxiliary gear ON/OFF fed at 220-240V; 50/60 Hz.

Item code	11.5000.0031.20
Product type	OUT
Category	Recessed
Family	E-Wall
Subfamily	E-Wall
Materials	Body built in die-cast aluminium with the frontal made of tempered glass and stainless steel.
Optical system	Luminaire built-in an opal diffuser that could be complemented with antiglare louver.
Installation instructions	Luminaire designed for wall recessed installed.

Pictograms

